OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SIGNAL TOWER, HALF DOME 90

H90K0243AGD
Signal tower,HALFDOME 90 24V AC/DC

- Compact (ready to use) LED signal tower in half dome design
- Tower is built and supplied according to customer‘s requirements
- Wide control voltage range



PRODUCT DESCRIPTION

The Half Dome 90 signal tower is a high quality option for signalling, with a pleasing look and 180° viewing angle the Half Dome is perfect for any high end signalling requirements.

- Visual-audible LED signal tower in half dome design
- For universal applications (industrial, building and others)
- Any colour combination and housing size (2 – 5 positions) available
- 6 lens colours, 3 housing colours (grey, chrome, black)
- LED steady light or LED flashing light for each position selectable
- High protection class IP 65 – suitable for outdoor and indoor
- For horizontal and vertical mounting
- Particular lens optics with reflective coating

- optimal signalling and visibility from each viewing angle (180°)
- moving bright LED light

- Optional piezo buzzer in upper housing area available

- tone types continuous and pulsing
- sound pressure individually adjustable ~70-90 dB (A)at 1M

- SPS-fit (leakage, inrush current)
- Available in nominal voltages 12 V ac/dc, 24 V ac/dc, 110/120 V ac and 230/240 V ac
- Certified to UL type 4/4X/13


TECHNICAL DATA


DATA


Lens colour	Green, Orange, Red
Housing Colour	Silver
IP class	IP65
Light source	LED
Light type	Green LED, Orange LED, Red LED
Supply voltage	24 V


Mounting	Wall
Nominal current max	0.043 A
Temperature operational min	-30 °C
Temperature operational max	50 °C

Terminal connection	2.5 mm²
Diameter	90 mm
Nominal current min	0.043 A

























































HOUSING COLOUR (1)

grey	G
chrome	C
black	B

NOMINAL VOLTAGE (2)

12 V AC/DC	12
24 V AC/DC	24
110/120 V AC	10
230/240 V AC	23

MODULES (3-8)

Module type (x)

HLL	LED steady light	L
HLB	LED flashing light	B
HDZ	Piezo buzzer, continuous and pulsing tone, 70-90 dB	DZ

Lens colour (x)

orange	1
red	2
clear	4
blue	5
green	6
yellow	7

Light modules | Tone module

HD | | | | | | | | |

1 2 3 4 5 6 7 8

2ND MODULE

This module is the 1st element of the order number.

1ST MODULE

This module is the 2nd element of the order number.