

OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SPR-PVC-AS METAL CONDUIT

2010.111.013

- Galvanized steel, PVC sheathed
- Good tensile strenght
- · Protects from mechanical stress



PRODUCT DESCRIPTION

SPR-PVC-AS is a highly flexible protective conduit made from galvanized steel with a PVC sheathing. Good resistance against oils and chemicals, IP68 rated.



Suitable for use in various applications in automation, machinery and equipment and electrical installations.

- Weatherproof conduit
- Resistant against seawater, oils and chemicals
- For outdoor applications and damp environments

TECHNICAL DATA

| Approvals | VDE |
|-----------------------------|------|
| Bending radius ±10% dynamic | 115 |
| Bending radius -10% static | 45 |
| Colour | Grey |
| Hose dimension AD | 17 |

| Inner dimensions | 13 mm |
|-----------------------------|-------------------------------|
| IP class | IP68 |
| Material | Galvanized steel, PVC coating |
| Outer dimensions | 17 mm |
| Pack size | 50 m |
| Temperature operational max | 90 °C |
| Temperature operational min | -25 °C |
| Туре | SPR-PVC-AS |
| Weight / m | 0.17 |





