

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ROHRFLEX® PA 12 PROTECTIVE CONDUIT

0236.202.006 Plastic tube-PA12 AD 10,0 Black

- Very flexible
- · Resistant against continuous bending
- Halogen-free



PRODUCT DESCRIPTION

ROHRflex PA 12 provides high flexibility needed in applications such as robot installations in- and outdoors. Both internally and externally corrugated. Good oil resistance.

| <u> </u> | |
|----------|--|

Supplied in full packages, also available in orange and grey colors.

TECHNICAL DATA

| Approvals | CE, VDE |
|-----------------------------|---------|
| Bending radius ±10% dynamic | 35 |
| Bending radius -10% static | 13 |
| Colour | Black |
| Fire rating | UL94-V2 |
| Hose dimension AD | 10 |
| Inner dimensions | 6.5 mm |

| Material | Polyamide |
|-----------------------------|----------------|
| Outer dimensions | 10 mm |
| Pack size | 50 m |
| Temperature operational max | 100 °C |
| Temperature operational min | -50 °C |
| Туре | ROHRFLEX -PA12 |
| Weight / m | 0.2 |

