OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CUBO O ENCLOSURES

OABP306013G
Enclosure Cubo O ABS Plain Grey Lid 300x600x130mm



- 200x200x132mm > 400x600x187mm
- Polycarbonate or ABS
- IP66/67
- Plain sides or Metric/PG knockouts

PRODUCT DESCRIPTION

Ensto Cubo O enclosures

Ensto Cubo O,C,W and P are a series of medium to large size enclosures available with plain sides, metric knockouts, flange knockouts, ready assemble with latches and hinges and a modular panel building system. Special features of the series allow mounting the cover onto the back of the base and include adjustable elevators for the base corner slots, enabling plates and panels to be mounted at any height

• Available with plain sides or with metric knockouts
• Available in 8 base sizes, one base depth and one cover height
• A 55 mm deep extension frame available for alternative depths in all sizes. Several extension frames can be used on top of each other in one enclosure.
• Cover and cover screws equipped with sealing holes
• Cover can also be mounted onto the back of the base
• Wide range of accessories available.

Contents of the product package:

A 132 mm deep standard enclosure includes:

• Enclosure base
• Cover
• Cover screws
• Mounting screws

A 187 mm deep standard enclosure includes:

• Enclosure base
• Cover
• Extension frame
• Cover screws
• Mounting screws
• Screws for the extension frame

Customising services available for this product:

• Machining
• Prints
• Colour service
• Assembly of components

TECHNICAL DATA

DATA

Width	300 mm
Depth	132 mm
Height	600 mm
Material	ABS plastic
Lid	Grey
IP class	IP66, IP67
Operating temperature from	-40 °C
Operating temperature to	80 °C
Temperature range, short term min	40 °C
Temperature range, short term max	120 °C