OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CUBO C (MEDIUM & LARGE ENCLOSURES.)

CPCF303013T
Enclosure Cubo C Polycarb Flange Clear Lid
300x300x130mm



- polycarbonate
- IP 66/67
- Knock outs for FL 13 / FL21 flange
- Raise frame, 55 mm

PRODUCT DESCRIPTION

Ensto Cubo C universal coverings are made of polycarbonate. Bottoms have knock-outs for FL13 / FL21 flanges on all sides. Standard color is gray RAL 7035, gray or transparent lid.

All dimensions follow 100mm modules the smallest 200x200 and the largest 400x600mm; depth 130 or 185 mm. For all sizes, there is a 55 mm deep extension frame for alternative depths.

Stackless adjustable mounting brackets (corner lifts) in the drawer latch make it possible to attach mounting plates and panels to the desired height.

The lower parts can be easily assembled into larger units, see also Ensto Cubo P Central Building System.

TECHNICAL DATA

Width	300 mm
Height	300 mm
Depth	132 mm
Lid	Transparent
Colour	Grey RAL 7035
Material	Polycarbonate
IP class	IP66, IP67
Operating temperature from	-40 °C
Operating temperature to	80 °C
Temperature range, short term min	-40 °C
Temperature range, short term max	120 °C