ORLACO FAMOS CAMERA

ORL0171070 Camera FAMOS 170° PAL

- Robust construction for extreme environments
- 12 or 24 V DC
- operating temperature -40 to +85 °C
- · Epoxy-filled, better protection against moisture





PRODUCT DESCRIPTION

These cameras are available in several different viewing angles to suit the various applications they can be used in. For example, if you want to see details in a long way, choose a narrower opening angle and instead you want a cross-section view, choose a further opening angle. Orlaco cameras are suitable for all types of vehicles, regardless of whether you need a power camera, back camera or side camera.

Orlaco's new FAMOS camera is not gas-filled as the traditional clover camera has been before, but it's epoxy-filled instead. This has provided better protection against moisture.

TECHNICAL DATA

Camera angle	170 °
Contacts	4-pole male
Image format	PAL
IP class	IP68, IP69K
Supply voltage dc max	24 V DC

Supply voltage dc min	12 V DC
Temperature operational max	85 °C
Temperature operational min	-40 °C
Vibration resistance	50g



 Electrical connections

 Front side of molded 4p male connector

 1 = Coax core
 = Video signal

 2 = Coax screen
 = Video GND

 3 = Red
 = 12...24V/DC

 4 = Black/orange
 = OV

 Shielding
 To connector housing

