



AUER PANEL MOUNTED BUZZER

812510313

Panel mount buzzer, Ø30mm, Black, 230-240 V ac, ESV

- Panel mounted buzzer with loud sound level
- Adjustable volume
- 3 selectable sound signals
- For mounting in drilled holes 22.5 mm or 30.5 mm



PRODUCT DESCRIPTION

Panel mounted buzzer with wide voltage range and high enclosure class, IP65. Excellent when you want to call for extra attention in a panel.


TECHNICAL DATA

Diameter	30 mm
Housing Colour	Black
IP class	IP65
Nominal current max	0,04 A
Number of optional modules	0
Number of tones	2
Sound level max	85 dB
Sound level min	80 dB
Supply voltage ac/dc min	10 V
Temperature operational max	60 °C
Temperature operational min	-25 °C
Terminal connection	2,5 mm ²
Tone frequency max	3500 Hz
Weight	30 g

Tone table

Tone and light selection on terminal			
La	N	Lb	Tone and light synchronized
X	X		pushing tone / LED flashing light
X	X	X	continuous tone / steady light

ESV



The sound pressure decreases by 6 dB when doubling the distance; the following distance table is to be seen as indication, as also factors like tone type, wind speed, wind direction, humidity, weather conditions etc. do influence the sound pressure level.

Distance (m)	65	70	75	80	85	90	92	94	96	98	100	102	104	106	108	110	112	114	116	118	120
1	59	64	69	74	79	84	86	88	90	92	94	96	98	100	102	104	106	108	110	112	114
2	55	60	65	70	75	80	82	84	86	88	90	92	94	96	98	100	102	104	106	108	110
3	51	56	61	66	71	76	78	80	82	84	86	88	90	92	94	96	98	100	102	104	106
5	45	50	55	60	65	70	72	74	76	78	80	82	84	86	88	90	92	94	96	98	100
10	39	44	49	54	59	64	66	68	70	72	74	76	78	80	82	84	86	88	90	92	94
20	35	40	45	50	55	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90
30		36	41	46	51	56	58	60	62	64	66	68	70	72	74	76	78	80	82	84	86
50			40	45	50	52	54	56	58	60	62	64	66	68	70	72	74	76	78	80	
100				39	44	46	48	50	52	54	56	58	60	62	64	66	68	70	72	74	
200					38	40	42	44	46	48	50	52	54	56	58	60	62	64	66		
500																					

The sound pressure decreases by 6 dB when doubling the distance



Justerbar volym
med hjälp av
potentiometer,
(ej ESK.)

