JOYSTICKS

Joystick heads & contacts

LM2A Joystick 2 Position Spring Return

- Mounts in Ø22.5 mm hole
- 2 or 4 way plus centre off
- Stable or spring return
- Centre position latched or unlatched





PRODUCT DESCRIPTION

Joystick heads are available in 2 or 4 way, stable or spring return and with latched (button to release) or non latched centre off. All heads come with a 3 position contact holder clip but the M11 contact blocks must be ordered separately.

The joystick heads require a special contact block (M11) that has 2 x N/O electrical contacts. The contacts will always be open when the head is in the centre off position and will close respectively in each of 2 positions.


A 2 way joystick can have 1 or 2 x M11 contact blocks to achieve 1 or 2 separate closed contacts in each of the 2 positions respectively excluding the centre off position.


A 4 way joystick requires 2 x M11 contact blocks to achieve a separate closed contact in each of the 4 positions excluding the centre off position.

TECHNICAL DATA

Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Function	Spring return
IP class	IP65
Positions	3
Protection class	II
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C







Kontaktfunktion 3-läges joystick

				Α	0	В
LM11	13		14	X		
	11	__	12			X
LM11	23		24			X
	21	__	22	X		

Joystic	ks												
	position					4	position						
	Two stock cur (LME)	STANDARD WITH	poven	CR HEA	4	1	I WO BLOCK CLIP (LME)	STANDARD WITH	ADVIDE:	* 104	a)	_	-
	Uhr ie Olip tocation	Seminal Numbers		Pesitio			UMm in Clip tocation	Terminal Numbers	A		enitio 0		ı
1	- 7	34	×	0.0	0 X	0.5.0		34	0 0	0 0	0 0	o ×	1
		34 12	0 1	0 0	0	-	1	14	0	0	00	00	-
	Four scook cur (LMIS				=	1	Four mock cur (LMES)						
	Ofe Leaden	Sereinal Numbers		Positio			Olg Location	Seminal Numbers	A		0		
		3-4	×	0 0	0 X			34 10	0	0 0	0 0	0 ×	1
1		94 12	0 X	0 0	x 0	0.0	i	14	0 X	×	0 0	00	0
	-	9-4 1-2		0 0	0 X	1	3	94	00	0	0	0 X	1
	140	3-4	0	0 0	×	1		14	0 ×	×	0	0 0	4