FAN HEATER 150 - 400 W PTC CS028/CSL028

02800.9-00 CS 028 150W Fan heater, 120V ac, clip fixing

- Very compact design
- Quiet operation
- Dynamic heating
- Quick fastener for DIN rail or screw assembly





PRODUCT DESCRIPTION

CS028/CSL028 range is a high performance PTC fan heater; it prevents the formation of condensation and provides an even temperature within the enclosure.

In has a very compact design and is well-suited for use in cabinets and enclosures where space is at a premium.

Because the heater is dual isolated with a plastic casing, the surface temperature never exceeds 50 °C on the 150/250W and 65 °C on the 400 W unit. This means the heater can be mounted relatively close to other components in the same installation, and there is no risk for heat damage.

You can choose between brackets for DIN rails or screw assembly.

TECHNICAL DATA

GENERAL DATA

| Heat output | 150 W |
|------------------|---|
| Nominal voltage | 120 V AC |
| Frequency | 50/60 Hz |
| Heater body | Plastic |
| Material of body | Plastic |
| Mounting | Clip on, DIN rail |
| Colour | Black |
| Number of fans | 1 |
| Connection type | 2-pole terminal for 2.5 mm ² cable |

| Starting current max | 6 A |
|------------------------------|-----------------------------|
| Recommended fuse (slow blow) | 10 A |
| Life span | 40 000 h @ +40 °C (+104 °F) |
| Air capacity | 13,8 m³/h |
| DIMENSIONS | |
| Height | 75 mm |
| Width | 65 mm |
| Depth | 90 mm |

0,3 kg

0,8 Nm

| Tightening torque for cable | |
|-----------------------------|--|
|-----------------------------|--|

SAFETY & APPROVALS

Weight

| Protection class | II (double insulated) |
|------------------------|--------------------------------------|
| IP class | IP20 |
| Approvals | CE, cULus, EAC, RoHS, UL, UL E150057 |
| Flammability class | UL94-V0 |
| Overheating protection | PTC temperature limiting |

RATED OPERATING CONDITIONS

| Operational temperature | -45°C +70°C |
|-------------------------|-------------|
| Storage temperature | -45°C +70°C |
| Operating humidity | < 90% RH |
| Humidity storage | <90% RH |
| | |
| Voltage max | 120 V ac |
| Voltage min | 120 V ac |

