

SWITCH DISCONNECTOR ACCESSORIES

0172395

Early Break Auxiliary Contact For 50A & 63A

- Terminal covers
- Auxillary contacts
- Handles
- Clutch drive & interlock kits
- IP65 sealing kits



PRODUCT DESCRIPTION

Accessories for switch disconnecter range.

- Junction blocks that snap onto switch body to terminate neutral or earth connections
- Auxillary block with N/C+N/O contacts - snap onto switch body for remote contactor switching
- Early break auxillary block - snap onto switch body for remote contactor switching
- Padlockable handles for screw or ø22mm hole mount in red/yellow or grey
- Handle & legend for screw or ø22mm hole mount in red/yellow
- Terminal covers
- Clutch drive kits in 3 options to accomodate different panel depths
- Door interlock shroud to ensure panel door can only be opened in OFF position
- IP65 gasket kits to increase front of panel protection from IP40 to IP65

TECHNICAL DATA

| | |
|-------------------------------------------------------|------------------------|
| Connection stranded wire with ferrule max | 2 x 2.5mm ² |
| Conventional free air thermal current I _{th} | 10 A |
| Rated insulation voltage U _i | 400 V |
| Rated operating current I _e (AC15/230V) | 6 A |
| Rated operating current I _e (AC15/400V) | 4 A |
| Rated uninterrupted current I _u | 10 A |
| Short circuit current with fuse gI/gG (A) | 10 A |
| Storage temperature max | 70 °C |
| Storage temperature min | -30 °C |
| Temperature operational max | 70 °C |

| | |
|-----------------------------|-------------------|
| Temperature operational min | -30 °C |
| Type | Auxiliary contact |

