

DATALOGIC - LIGHT BEAM SG BODY COMPACT MUTING

SG4-S2-050-PP-W
SG4-S2-050-PP-W 2 Beam Type 4

- Range up to 50 m
- Built-in muting
- "T" and "L" solutions



PRODUCT DESCRIPTION

TECHNICAL DATA

Additional features	EDM, reset functions
Approvals	CE, cULus, TÜV
Cable connection receiver	Receiver M12, 8-pole shielded + M12, 5-pole for muting
Cable connection transmitter	Transmitter M12, 4-pole, shielded + M12, 5-pole for muting
Cable length max	50 m
Contact current max	0,5 A
Distance max	50 m
Function	Manual/automatic restart, EDM
In compliance with	EMC, LVD, MD
IP class	IP65
Material of body	Aluminium
Number of beams	2
PL	e (EN ISO 13849-1)
Power consumption	Transmitter 1,6W. Receiver 4,2 W. (without load)
Protection height	500 mm
Range	0,5-50 m

Safe outputs	2 OSSD
SFF	98,93 %
SIL	3 (EN IEC 61508)
Supply voltage	24 V DC, stabilized
Supply voltage	24 V DC
Temperature operational max	55 °C
Temperature operational min	0 °C
Type	4
Voltage tolerance	±20 %

