



## KUEBLER - INCREMENTAL ENCODER, SENDIX H120

SERIE H120



- High durability
- Many mounting options
- High degree of enclosure
- Wide temperature range



### PRODUCT DESCRIPTION

The Sendix H120 series is designed to fit in tough environments. Specialized for high voltage motors, generators, steel and crane industry. The sensor has a high enclosure degree, IP66, IP67 and a wide temperature range -40 to +100 ° C. It is also equipped with "HD-Safety Lock™, which includes double gaskets, against moisture and dust. All layers are also sturdier and stronger.

The many choices of contact types make this pulse sensor very flexible, sometimes the optical fiber, M12, M23 and terminal boxes are selected. The H120 can be delivered with a fastening lever in different lengths.

Please refer to the image below for ordering information.

Order code Hollow shaft version		8.H120 . XXXXX . XXXX
		Type      a   b   c   d      e
<b>a</b> Flange	<b>c</b> Output circuit / power supply	
1 = without mounting aid	4 = RS422 (with inverted signal) / 5 V DC	
2 = with fastening arm 70 mm [2.76"] <sup>2)</sup>	1 = RS422 (with inverted signal) / 10 ... 30 V DC	
3 = with fastening arm 100 mm [3.93"] <sup>2)</sup>	5 = push-pull (with inverted signal) / 10 ... 30 V DC	
4 = with fastening arm 150 mm [5.91"] <sup>2)</sup>	6 = push-pull (with inverted signal) / 10 ... 30 V DC, power version up to 350 m	
5 = with stator coupling, ø 119 mm [4.69"]	B = optical fiber + RS422 (with inverted signal) / 5 V DC <sup>3)</sup>	
	A = optical fiber + RS422 (with inverted signal) / 10 ... 30 V DC <sup>3)</sup>	
	C = optical fiber + push-pull (with inverted signal) / 10 ... 30 V DC <sup>3)</sup>	
<b>b</b> Through hollow shaft	<b>d</b> Type of connection	
2 = ø 16 mm [0.63"]	1 = radial cable, 1 m [3.28'] PVC	
3 = ø 20 mm [0.79"]	A = radial cable, special length PVC *)	
5 = ø 25 mm [0.98"]	2 = radial M12 connector, 8-pin, ccw	
7 = ø 28 mm [1.10"]	4 = radial M23 connector, 12-pin, ccw	
6 = ø 1"	D = radial M23 connector, 12-pin, cw	
Blind hollow shaft, with central fastening insertion depth max. 53 mm [2.09"]	K = terminal box with plug-in spring terminal connectors, rotatable through 180°	
A = ø 12 mm [0.47"]	L = optical fiber connector + radial M23 connector, 12-pin, cw <sup>4)</sup>	
B = ø 16 mm [0.63"]	*) Available special lengths (connection type A):	
Blind hollow shaft, cone with central fastening insertion depth max. 22.5 mm [0.89"]	2, 3, 5, 8, 10, 15 m [6.56, 9.84, 16.40, 26.25, 32.80, 49.21']	
K = ø 17 mm [0.67"], 1 : 10	order code expansion .XXXX = length in dm	
	ex.: 8.H120.121A.2048.0030 (for cable length 3 m)	
	<b>e</b> Pulse rate	
	50, 360, 512, 600, 1000, 1024, 1500, 2000, 2048, 2500, 4096, 5000	
	(e.g. 360 pulses => 0360)	
	Optional on request	
	- other pulse rates	
	- Ex 2/22 <sup>5)</sup>	

### TECHNICAL DATA

