




## KUEBLER - INCREMENTAL ENCODER MINIATURE SERIES 2400/2420 SERIE 2400

- House diameter Ø24 mm
- Cable connection 2 metres
- Miniature version.
- Temperature compensation



### PRODUCT DESCRIPTION

Model 2400/2420 is a pulse generator series for industrial applications for confined spaces or where the sensor needs to be lightweight. The models 2400/2420 have a so-called Push-Pull output which means that it can be connected to an input that is either PNP or NPN. Output signals are A, B, 0. They also have inverted signals to be connected to inputs that are adapted for malfunction.

Please refer to the images below for ordering information.

Order code	05.2400	. XXXXX .	XXXX
Shaft version	Type	a b c d	e
<b>a</b> Flange <u>1 = ø 24 mm [0.94"]</u> 3 = ø 28 mm [1.10"] 2 = ø 30 mm [1.18"]	<b>b</b> Shaft (ø x L) <u>1 = ø 4 x 10 mm [0.16 x 0.39"]</u> 3 = ø 5 x 10 mm [0.20 x 0.39"], with flat 2 = ø 6 x 10 mm [0.24 x 0.39"]  4 = ø 1/4" x 10 mm [1/4" x 0.39"], with flat <sup>1)</sup> 6 = ø 6 x 10 mm [0.24 x 0.39"], with flat <sup>1)</sup>	<b>c</b> Output circuit / power supply 1 = push-pull (without inverted signal) / 5 ... 24 V DC 2 = push-pull (with inverted signal) / 5 ... 24 V DC 3 = push-pull (without inverted signal) / 8 ... 30 V DC <u>4 = push-pull (with inverted signal) / 8 ... 30 V DC</u>  <b>d</b> Type of connection <u>1 = axial cable, 2 m [6.56'] PVC</u> A = axial cable, special length PVC *) 2 = radial cable, 2 m [6.56'] PVC B = radial cable, special length PVC *)  *) Available special lengths (connection types A, B): 3, 5, 8, 10, 15 m [9.84, 16.40, 26.25, 32.80, 49.21'] order code expansion .XXXX = length in dm ex.: 05.2400.122A.1024.0030 (for cable length 3 m)	<b>e</b> Pulse rate 4, 6, 8, 10, 16, 20, 25, 36, 40, 50, 60, 80, <u>100</u> , 120, 125, 180, 200, 250, 300, <u>360</u> , 400, 500, <u>512</u> , <u>1000</u> , <u>1024</u> (e.g. 360 pulses => 0360)  Stock types 05.2400.1122.0050 05.2400.1122.0360 05.2400.1122.0500 05.2400.1122.1000 05.2400.1122.1024  Optional on request - other pulse rates

Order code  
Hollow shaft

05.2420  
Type

1XXX.XXXX  

a
b
c
d
e

**a** Flange  
1 =  $\varnothing$  24 mm [0.94"]

**b** Blind hollow shaft  
(insertion depth max. 14 mm [0.55"])  
1 =  $\varnothing$  4 mm [0.16"]  
2 =  $\varnothing$  6 mm [0.24"]

4 =  $\varnothing$  1/4" <sup>1)</sup>

**c** Output circuit / power supply  
1 = push-pull (without inverted signal) / 5 ... 24 V DC  
2 = push-pull (with inverted signal) / 5 ... 24 V DC  
3 = push-pull (without inverted signal) / 8 ... 30 V DC  
**4 = push-pull (with inverted signal) / 8 ... 30 V DC**

**d** Type of connection  
**1 = axial cable, 2 m [6.56'] PVC**  
A = axial cable, special length PVC \*)  
2 = radial cable, 2 m [6.56'] PVC  
B = radial cable, special length PVC \*)  
\*) Available special lengths (connection types A, B):  
3, 5, 8, 10, 15 m [9.84, 16.40, 26.25, 32.80, 49.21']  
order code expansion .XXXX = length in dm  
ex.: 05.2420.122A.1024.0030 (for cable length 3 m)

**e** Pulse rate  
4, 6, 8, 10, 16, 20, 25, 36, 40, 50, 60,  
80, **100**, 120, 125, 180, 200, 250, 300,  
**360**, 400, 500, **512**, **1000**, **1024**  
(e.g. 360 pulses => 0360)

Stock types  
05.2420.1212.0500  
05.2420.1222.0500  
05.2420.1222.1000  
05.2420.1222.1024  
  
Optional on request  
- other pulse rates

TECHNICAL DATA

Connection	Cable
Housing diameter	24 mm
IP class	IP64
Mounting	Shoulder
Output	Push/Pull
Pulse max	1024
Sensor type	Incremental
Shaft diameter max	6 mm
Shaft diameter min	4 mm
Supply voltage dc max	30 V DC
Supply voltage dc min	5 V DC
Temperature operational max	85 °C
Temperature operational min	-20 °C
Version	Multiturn

