



## ASCO - 2/2 SERVO-CONTROLLED 1/4"-3/4"

SCB223A125  
Solenoid valve 2/2 NC 1/4" 230/50



- Normally closed
- For high pressure
- Standard working pressure 0.7 bar to 100 bar
- Housing in brass or stainless



### PRODUCT DESCRIPTION

### TECHNICAL DATA

Close delay	15 ms
Connection	1/4 BSP
Differential air pressure max	100 bar
Differential oil pressure max	100 bar
Differential pressure max	100 bar
Differential pressure min	0,7 bar
Differential water pressure max	100 bar
Flow factor / flow coefficient	1,3
Flow max	21,7 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
IP class	IP65
Material body	Brass
Material coil	Epoxy
Material flask	Stainless steel
Material glide ring	PTFE

<b>Material of seals</b>	NBR
<b>Material piston seal</b>	PTFE
<b>Material plunger</b>	Stainless steel
<b>Material plunger tube</b>	Stainless steel
<b>Material seat</b>	Brass
<b>Material seat seal</b>	Urethane
<b>Material short-circuit ring</b>	Copper
<b>Power consumption</b>	16,7 W
<b>Pressure max</b>	100 bar
<b>Response time off</b>	60 ms
<b>Temperature of media from</b>	-20 °C
<b>Temperature of media to</b>	90 °C
<b>Temperature operational max</b>	50 °C
<b>Temperature operational min</b>	-20 °C
<b>Throughput</b>	8 mm
<b>Type of valve</b>	Solenoid valve
<b>Weight</b>	0,7 kg
<b>Viscosity max</b>	65 cSt
<b>Voltage AC</b>	230 V

