



Angle seat valve 3/8" NC "MINI"

- 

## TECHNICAL DATA

Connection	3/8 BSP
Connection air	1/8 BSP
Differential air pressure max	16 bar
Differential oil pressure max	16 bar
Differential pressure max	16 bar
Differential pressure min	0 bar
Differential steam pressure max	10 bar
Differential water pressure max	16 bar
Flow factor / flow coefficient	2,8
Flow max	47 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material body	Stainless steel 316L
Material box stuffing	PTFE
Material controls	Fiberglass reinforced polyamide
Material of body	Stainless steel 316L

<b>Material of seals</b>	PTFE
<b>Material packing</b>	Stainless steel
<b>Material piston rod</b>	Stainless steel
<b>Material piston rod seal</b>	Stainless steel 303
<b>Material piston seal</b>	PTFE
<b>Material scraping seal</b>	FPM
<b>Pilot pressure max</b>	10 bar
<b>Pilot pressure min</b>	4 bar
<b>Pressure max</b>	16 bar
<b>Temperature of media from</b>	-10 °C
<b>Temperature of media to</b>	184 °C
<b>Temperature operational max</b>	60 °C
<b>Temperature operational min</b>	-10 °C
<b>Throughput</b>	10 mm
<b>Weight</b>	0,35 kg
<b>Viscosity max</b>	600 cSt

