



## ASCO - 2/2 STEAM VALVE 3/8"-3/4"

SCE222D001

Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Media temperature up to +180 °C
- Working pressure 0 to 9 bar steam
- Housing in brass



### PRODUCT DESCRIPTION

### TECHNICAL DATA

|                                |                        |
|--------------------------------|------------------------|
| Close delay                    | 75 ms                  |
| Connection                     | 3/8 BSP                |
| Differential pressure max      | 9 bar                  |
| Differential pressure min      | 0 bar                  |
| Flow factor / flow coefficient | 2,4                    |
| Flow max                       | 40 l/min               |
| Function 1                     | 2/2                    |
| Function 2                     | Normally Closed (SPST) |
| IP class                       | IP65                   |
| Material body                  | Brass                  |
| Material coil                  | Epoxy                  |
| Material flask                 | Brass                  |
| Material of seals              | PTFE                   |
| Material piston ring           | PTFE flask filled      |
| Material plunger               | Stainless steel        |
| Material plunger tube          | Stainless steel        |

|                                    |                 |
|------------------------------------|-----------------|
| <b>Material seat</b>               | Brass           |
| <b>Material short-circuit ring</b> | Copper          |
| <b>Material spring</b>             | Stainless steel |
| <b>Power consumption</b>           | 16,7 W          |
| <b>Pressure max</b>                | 10 bar          |
| <b>Response time off</b>           | 100 ms          |
| <b>Temperature of media from</b>   | -20 °C          |
| <b>Temperature of media to</b>     | 184 °C          |
| <b>Temperature operational max</b> | 40 °C           |
| <b>Temperature operational min</b> | -20 °C          |
| <b>Throughput</b>                  | 16 mm           |
| <b>Type of valve</b>               | Solenoid valve  |
| <b>Weight</b>                      | 1,3 kg          |
| <b>Voltage AC</b>                  | 230 V           |

