



## ASCO - 2/2 PROPORTIONAL VALVE 3/8"

SCE202A023VS3

Proportional valve 2/2 NC 3/8" 24VDC

- Normally closed
- Large flow
- Working pressure 0 to 4 bar
- Housing in brass or stainless



### PRODUCT DESCRIPTION

### TECHNICAL DATA

Connection	3/8 BSP
Differential air pressure max	4 bar
Differential pressure min	0 bar
Differential pressure vacuum max	1 bar
Flow factor / flow coefficient	0,24
Flow max	4 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
IP class	IP65
Material body	Brass
Material coil	Epoxy
Material glide ring	PTFE
Material of seals	FPM
Material plunger	Stainless steel
Material plunger tube	Stainless steel
Material seat	Brass

<b>Material spring</b>	Stainless steel
<b>Power consumption</b>	8 W
<b>Pressure max</b>	35 bar
<b>Sensitivity</b>	<2%
<b>Temperature of media from</b>	-10 °C
<b>Temperature of media to</b>	90 °C
<b>Temperature operational max</b>	75 °C
<b>Temperature operational min</b>	-10 °C
<b>Throughput</b>	3,2 mm
<b>Weight</b>	0,5 kg
<b>Viscosity max</b>	21 cSt
<b>Voltage dc</b>	24 V

