



ASCO - 2/2 PROPORTIONAL VALVE 1/8"

SCG202A201VS3

Proportional valve 2/2 NC 1/8" 24VDC

- Normally closed
- Compact version
- Working pressure 0 to 8 bar
- Housing in brass or stainless



PRODUCT DESCRIPTION

TECHNICAL DATA

Connection	1/8 BSP
Differential air pressure max	8 bar
Differential oil pressure max	5 bar
Differential pressure min	0 bar
Differential pressure vacuum max	1 bar
Differential water pressure max	5 bar
Flow factor / flow coefficient	0,05
Flow max	0,7 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
IP class	IP65
Material body	Brass
Material coil	Epoxy
Material glide ring	PTFE
Material plunger	Stainless steel

Material plunger tube	Stainless steel
Material seat	Brass
Material seat seal	FPM
Material spring	Stainless steel
Power consumption	6,3 W
Pressure max	35 bar
Sensitivity	<1%
Temperature of media from	0 °C
Temperature of media to	50 °C
Temperature operational max	40 °C
Temperature operational min	0 °C
Throughput	1,2 mm
Weight	0,2 kg
Viscosity max	50 cSt
Voltage dc	24 V

