



MOLEX - MPM DIN FORM B INDUSTRIAL / DIN FORM B

22200TC320R

Form Industrial, 2P+Earth, Ext Thread, C3, 24V, IP67, Red

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- 11 mm or 10 mm connector distance EN175301-803 (DIN43650-B Industrial/-B)



PRODUCT DESCRIPTION

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

TECHNICAL DATA

Cable diameter max	9 mm
Cable diameter min	4 mm
Circuit	C3: LED & diode
Colour LED	Red
Contact resistance	≤15 mΩ
Cross section max	1,5 mm ²
Current max	16 A
Housing Colour	Transparent
Housing material	Polyamide
IP class	IP67
LED indicator	Yes
Manufacturer part no.	1212080055
Material packing	NBR
Number of poles	2 + earth

Rated voltage	24 V DC
Screw and gasket	Integrated NBR Gasket & IP67 screw
Temperature operational max	90 °C
Temperature operational min	-40 °C

