



ASCO - 238 SERIES PILOT OPERATED

2/2

SCG238A044
Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- 3/8" up to 2" pipe size
- Air, inert gas & water
- Housing in brass or stainless steel
- Flow rates from 2.1 up to 34 m3/h



PRODUCT DESCRIPTION

TECHNICAL DATA

Connection	G3/8
Differential air pressure max	10 bar
Differential pressure max	10 bar
Differential pressure min	0 bar
Differential water pressure max	10 bar
Flow factor / flow coefficient	2,1
Flow max	35 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
IP class	IP65
Material body	Brass
Material coil	Epoxy
Material internal parts	Stainless steel
Material membrane	NBR
Material of seals	NBR

Material plunger	Stainless steel
Material plunger tube	Stainless steel
Material seat	Brass
Material short-circuit ring	Copper
Power consumption	6 W
Pressure max	16 bar
RSK number	4528043
Temperature of media from	-20 °C
Temperature of media to	85 °C
Temperature operational max	75 °C
Temperature operational min	-20 °C
Throughput	12,5 mm
Weight	0,55 kg
Viscosity max	40 cSt
Voltage AC	230 V

