

DE-UU012A11100 Non-return valve, ½", SS/PFA/EPDM

- Designed for minimal pressure surfaces
- · Vertical mounting for an improved seal
- Quick and easy installation
- Connection: Welding end
- Sealing types: PFA FKM EPDM PTFE



1600-1630

## PRODUCT DESCRIPTION

Our products are of high quality and design that meet the strongest requirements of process technology and are the ideal solution for Food, Brewery, Cosmetics and Pharmaceutical processes!

## Tehcnical Advantages:

- · 1/2 "'- DN 125
- $\cdot$  Interior surface roughness Ra = 0.8  $\mu m$
- $\cdot$  Vertical mounting for an improved seal and eliminate retention
- · Fast and easy disassembly
- · Connection: Welding ends
- · Multiple packing types: PFA FKM EPDM.
- · Approvals .: 3A ATEX DESP 3.1 2.1 E1935 / 2004 CE REACH ANIA

## **TECHNICAL DATA**

Certificate	3.1 EN10204
Connection type	Weld ends
Design norm	SMS
Housing	PFA/EPDM
Inner diameter	9,4 mm
Material quality	1.4404
Operating pressure max	10 bar
Outer diameter	12,7 mm
Output	90 Mbar
Surface finish	RA<0,8/1,2µm
Temperature operational max	120 °C
Temperature operational min	0 °C

Weight 0,3 kg