

## EARTH TERMINALS - SCREW ON - SL 2.5-35 MM<sup>2</sup>, SSL 50-70MM<sup>2</sup>

SL, SSL

1441.2

SL 16/35 EX, Screw clamp 16mm Ex certified earth terminal

- Screw to rail construction
- SL - Material polyamide 6.6 - UL94-V2
- Temperature resistance -40 °C...+105 °C
- SSL - Material polyamide 6.6 - UL94-V0
- Temperature resistance -40 °C...+120 °C



### PRODUCT DESCRIPTION

The RK and SL range is the original traditional terminal range feed-through featuring the proven screw-connection system and screw in cross connectors.

This range is available with the 'multi-foot' construction, so will fit on TS35 and TS15 – 'Top Hat' rail or the less common TS32 – 'G-Rail', still used in some applications today.

The range also includes disconnect terminals, fused terminals, actuator, sensor, motor-connection terminals and a range of direct mount options.

For applications where space is at a premium the TS15 range is small and compact, but can still accommodate 4mm<sup>2</sup> cable sizes.

## TECHNICAL DATA

### GENERAL DATA

Rated wire cross section	16 mm <sup>2</sup>
Colour	Green/yellow
Mounting	TS 35
Overvoltage category	III
Contamination degree	3
Approvals	UL, CSA, CSA US, cUL, KEMA KUR, NEMKO, EAC
Explosion proof	Yes

### DIMENSIONS

Length	50 mm
Width	12 mm

Height TS 35/7.5	63 mm
------------------	-------

## CONNECTION DATA

Connections	2
Number of levels	1
Plug gauge acc. EN 60 947-1	B7
Cross section single wire from	2,5 mm <sup>2</sup>
Cross section single wire to	16 mm <sup>2</sup>
Cross section stranded wire from	2,5 mm <sup>2</sup>
Cross section stranded wire to	16 mm <sup>2</sup>
Cross section stranded with ferrule from	2,5 mm <sup>2</sup>
Cross section stranded with ferrule to	16 mm <sup>2</sup>
Rated wire cross section from (AWG)	10
Rated wire cross section to (AWG)	4
Stripping length	15 mm
Screw size	M 5
Screw type	Slotted
Torque min	2 Nm
Torque max	4 Nm

## MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V2
Operating temperature from	-40 °C
Operating temperature to	105 °C

## APPROVALS

EX approvals	NEMKO ATEX 1136 U
UL test standard	UL 1059
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011
KEMA KEUR test standard	EN 60947-7-2:2009

## ADDITIONAL DATA

<b>Tariff code</b>	85369010
<b>Country of origin</b>	DE
<b>Weight</b>	54,8 g
<b>Pack size</b>	50
<b>Type of terminal</b>	Screw Terminals, DIN Rail terminals
<b>Nemko test standard</b>	EN 60947-7-2:2002