SCREW TERMINAL COVERS AND WARNING SIGNS

AD, SAD, FAD, ZAD, TWMF

2958.2 AD 3/1000 mm, Transparent cover profile

- Assembly cover profiles
- Individual terminal covers
- Yellow or White
- Transparent cover profile
- RRK Cross connect covers



ZCONTACLIP

PRODUCT DESCRIPTION

Some regulations require that the mains power terminals must be covered.

This then discourages any operation of the screws or cross connector while 'Live'.

The EA, AD, SAD, FAD and ZAP covers are mainly available in yellow (labelled with a lightning flash) are used to cover the cross connect channel and screw holes of the terminal.

EA, AD & SAD covers are for the screw terminal range, where the FAD are for pressure spring and ZAD are for the tension spring range.

The BS 1 marker pen or the EMS labelling system can be used to label the white variants. The AD 4, is designed to cover four terminals of various sizes and is secured by two plastic screws.

The AQ 4 is used on the older RK series of scrfew terminals and covers the cross connect channel only, to cover the screw in cross connectors.

To complete the range the AD 3 is a transparent cover that can be cut to length and mounted using the TWMF partition plates.

TECHNICAL DATA

GENERAL DATA

Colour	Transparent	
DIMENSIONS		
Length	90 mm	
Width	1000 mm	
Height	68,5 mm	
MATERIALS		
Material	Polyamide 6.6	
Flammability class	UL94-V2	

Operating temperature from	-40 °C
Operating temperature to	105 °C
ADDITIONAL DATA	
Tariff code	39162000
Country of origin	DE
Weight	320 g
Pack size	1