

N30H

High voltage DC digital panel meter for measurement of d.c. current and d.c. voltage up to 5 A and 600 V.

N30H10XX

Panel Meter, 2x OC Outputs, 85-253V ac



- DC current and voltage upto 600V
- Wide voltage, AC/DC control
- 5 Digit, 3 colour programmable display

PRODUCT DESCRIPTION

Please refer to the image below for ordering information.

Part number key

Digital panel meter	N30H -	X	X	XX	XX	X
Supply voltage:						
85..253 V a.c./d.c.	1					
20..40 V a.c./d.c.	2					
Additional outputs:						
lack	0					
RS-485, analog outputs	1					
RS-485, analog outputs switched-over relay outputs AL3, AL4	2					
Unit:						
code number of the unit acc. table 2				XX		
Kind of execution:						
standard					00	
custom-made					XX	
Acceptance tests:						
without extra additional requirements						8
with an extra quality inspection certificate						7
acc. to customer's agreement						X

TECHNICAL DATA

Additional functions	<p>Conversion of any measured value into current or voltage analog signal.</p> <p>Storage of minimal and maximal values for all measured quantities. 21-point rescaling for the measured value (does not apply to N30P and N27P).</p> <p>Password protection. Programmable current and voltage transformer ratio (applies to N27P and N30P).</p>
Class	0.1
Digital interface	RS-485 Modbus Slave - Option

Dimensions	96 x 48 x 93 mm
Display	Yes
Input type	d.c. current 6 A, d.c. voltage 600 V
IP class	IP65
Mounting	Panel mount
Number of digits	5
Number of rows	1
Outputs	2 relays (NO)
Supply voltage	85-253V ac/dc
Temperature operational max	55 °C
Weight	0,2 kg

