

UNINSULATED RING SHAPED LUGS – QKS

QKS

30807.0 QKS 1/U/M4, 1mm² Seamed cable lug, M4

- Heat resistant up to 125 °C
- Soldered; DIN EN13599
- Size range 0.5 mm²...240 mm²
- Seamed version



PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The galvanised QKS seamed ring shaped lugs start at 0.5mm² through 240mm² (M2.5/M16).

 $To \ complete \ the \ range, \ a \ selection \ of \ un-insulated \ SKS \ pin \ crimp \ and \ STV \ butt \ connectors \ are \ also \ available.$

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Cross section min	0,5 mm ²
Cross section max	1 mm²
Metric connecting thread size	M 4
Ring hole diameter	4,3 mm
Conductor shape	Ring shape acc.DIN 46234
D (I) ((AWO)	20
Rated wire cross section from (AWG)	20
Rated wire cross section from (AWG) Rated wire cross section to (AWG)	18

DIMENSIONS

Width of ring	8 mm
Length to middle of ring	11,8 mm
Length of feed-in funnel	4,8 mm

Diameter of feed-in funnel	1,6 mm
Stripping length	4,8 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	Yes
Operating temperature to	125 °C

APPROVALS

DIN approvals EN 13599

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	0,73 g
Pack size	100

