

## INSULATED BOOTLACE FERRULES FOR DUAL CABLES

2794.0

HZL 0.5-D 0.5 x 14mm, Dual Ferrule, White

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

The special shape of the plastic collar makes it easy to feed in two wires in one wire-end ferrule.

## TECHNICAL DATA

### GENERAL DATA

Colour	White
Cross section max	0,5 mm <sup>2</sup>
Rated wire cross section to (AWG)	20
Standard	UL (DIN)/French Standard

### DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	11 mm
Thickness of collar	0,3 mm
Thickness of tube	0,15 mm
Diameter of tube	1,4 mm

### MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

### APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0,12 g
Pack size	500

