


# INSULATED BOOTLACE FERRULES FOR DUAL CABLES

2997.0

HZL 1.5 L-D, 1.5 x 18mm, Dual Ferrule, Black

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



## PRODUCT DESCRIPTION

The special shape of the plastic collar makes it easy to feed in two wires in one wire-end ferrule.

## TECHNICAL DATA

### GENERAL DATA

|                                   |                          |
|-----------------------------------|--------------------------|
| Colour                            | Black                    |
| Cross section max                 | 1,5 mm <sup>2</sup>      |
| Rated wire cross section to (AWG) | 16                       |
| Standard                          | UL (DIN)/French Standard |

### DIMENSIONS

|                     |         |
|---------------------|---------|
| Length              | 26 mm   |
| Length of tube      | 18 mm   |
| Stripping length    | 21 mm   |
| Thickness of collar | 0,3 mm  |
| Thickness of tube   | 0,15 mm |
| Diameter of tube    | 2,2 mm  |

### MATERIALS

|                |              |
|----------------|--------------|
| Conductor tube | Copper alloy |
|----------------|--------------|

|                            |                            |
|----------------------------|----------------------------|
| Contact surface            | Galvanic tin-plated, shiny |
| Plastic collar             | Polypropylene-homopolymer  |
| Operating temperature from | -5 °C                      |
| Operating temperature to   | 105 °C                     |

### APPROVALS

|                  |     |
|------------------|-----|
| DIN 46228-4:1990 | Yes |
| DIN 46228-1:1992 | No  |

### ADDITIONAL DATA

|                   |          |
|-------------------|----------|
| Tariff code       | 85369010 |
| Country of origin | DE       |
| Weight            | 0,3 g    |
| Pack size         | 100      |

