

## INSULATED BOOTLACE FERRULES FOR DUAL CABLES

3039.0

HZL 2.5 HL-T, 2.5 x 21mm, Dual Ferrule, Grey

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

The special shape of the plastic collar makes it easy to feed in two wires in one wire-end ferrule.

## TECHNICAL DATA

### GENERAL DATA

Colour	Grey
Cross section max	2,5 mm <sup>2</sup>
Rated wire cross section to (AWG)	14
Standard	French Standard

### DIMENSIONS

Length	21 mm
Length of tube	12 mm
Stripping length	15 mm
Thickness of collar	0,4 mm
Thickness of tube	0,15 mm
Diameter of tube	2,8 mm

### MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

### APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	EEC
Weight	0,22 g
Pack size	100

