


INSULATED BOOTLACE FERRULES

2788.0

H 120,0/50, 120.0 x 50mm Ferrule, Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

If the individual strands at the ends of finely stranded wires need to be protected due to frequent connecting, then our CONTA-CLIP wire-end ferrules are an ideal solution. The ferrules must be crimped gas-tight with the ends of the wires. A simply distortion caused by the clamping force is not adequate. The wire-end ferrules can be crimped easily and securely with CONTA-CLIP crimping pliers. The resulting connections function properly both electrically and mechanically.

- Collar feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated

TECHNICAL DATA

GENERAL DATA

Colour	Blue
Cross section max	120 mm ²
Rated wire cross section to (AWG)	4/0
Standard	German Standard

DIMENSIONS

Length	50 mm
Length of tube	30 mm
Stripping length	36 mm
Thickness of collar	0,7 mm

Thickness of tube	0,5 mm
Diameter of collar	21 mm
Diameter of tube	16,5 mm

MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	9,21 g
Pack size	25

