

## UNINSULATED BOOTLACE FERRULES

2228.0

H 10.0/12, 10.0 x 12mm, Uninsulated Ferrule

- Bootlace ferrules without plastic collars
- For wires from 0.5...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated
- DIN 46228 sheet 1/3.73



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

|                                   |                    |
|-----------------------------------|--------------------|
| Colour                            | Natural            |
| Cross section max                 | 10 mm <sup>2</sup> |
| Rated wire cross section to (AWG) | 8                  |

#### DIMENSIONS

|                    |        |
|--------------------|--------|
| Length             | 12 mm  |
| Stripping length   | 12 mm  |
| Thickness of tube  | 0,2 mm |
| Diameter of collar | 5,8 mm |
| Diameter of tube   | 4,5 mm |

#### MATERIALS

|                          |                            |
|--------------------------|----------------------------|
| Conductor tube           | Copper alloy               |
| Contact surface          | Galvanic tin-plated, shiny |
| Operating temperature to | 120 °C                     |

#### APPROVALS

|                  |     |
|------------------|-----|
| DIN 46228-4:1990 | No  |
| DIN 46228-1:1992 | Yes |

**ADDITIONAL DATA**

|                   |          |
|-------------------|----------|
| Tariff code       | 85369010 |
| Country of origin | DE       |
| Weight            | 0,34 g   |
| Pack size         | 500      |