

## UNINSULATED PIN TERMINALS - SKS

### SKS

30881.0

SKS 1/U, 1mm<sup>2</sup> pin-shaped cable lug

- Pin crimps for cable size 0.5 mm<sup>2</sup> to 95 mm<sup>2</sup>
- Pin shaped acc. to DIN 46230 and similar
- Cu-ETP acc. to DIN EN13599, soldered, galv. Sn
- Heat resistant to +125 °C



### PRODUCT DESCRIPTION

Contac-Clip have a range of tin-plated copper un-insulated pin crimp lugs (DIN 46230) that range from 1mm<sup>2</sup> up to 95mm<sup>2</sup>.

This range has an operating temperature of up to 125°C and conform to DIN EN13599.

## TECHNICAL DATA

### GENERAL DATA

Colour	Natural
Cross section min	0,5 mm <sup>2</sup>
Cross section max	1 mm <sup>2</sup>
Conductor shape	Pen shape acc.DIN 46230
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	18

### DIMENSIONS

Length	18,3 mm
Length of feed-in funnel	5 mm
Stripping length	5 mm

### MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	Yes
Operating temperature to	125 °C

### APPROVALS

DIN approvals	EN 13599
---------------	----------

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	0,67 g
Pack size	100

