

AC66B3-378 230V 1 ph 378rpm 0.6Nm B3 mount

- Single or three phase
- 9 to 74W delivered power
- Up to 5Nm rated torque
- B3 foot or B5 flange mounting
- IP65 as standard





PRODUCT DESCRIPTION

High quality, designed from the ground up to IP65 rated compact gear motor.

Physically smaller than the majority of similar powered gear motors due to the use of high quality components in precision manufacturing.

Ideally suited to many applications, including label and packaging machines, conveyors, pharmaceutical and medical machinery

MOTOR: Asynchronous single or three phase with 2 or 4 poles, totally enclosed with external ventilation. Thermal safety cutout on single phase model. Class F winding. IP65 protection according to CEI EN 60529.

GEAR UNIT: Casing in die-cast aluminium. Case-hardened and hardened gear pairs with shafts rotating on roller bearings. Lubrication with long-life oil. Sealing rings made in special rubber for high temperatures. 15 gear ratios (i) available, from 7.4 to 441.9. Rated torque 5 Nm. Version B3 or B5.

On request, motor may be supplied with electromagnetic brake at 230Va.c, marked with the letter KA (ACKA), or at 24Vd.c, marked with the letter KB (ACKB), see specifications on "BRAKE DATA"

2D and 3D drawings available here

TECHNICAL DATA

Capacitor	2.5 μF
Input voltage ac	230V
Nominal speed	378 rpm
Nominal torque	0,6 Nm
Output power	27 W
Rated current	0.34A A
Ratio	7.4:1

