IDEM SWITCH WITH IDIS-1 KEY

190050A IDIS-1 M20 '2NC 1NO' - angled actuator

- Perfect for small covers
- 8 key entry positions
- Small dimensions
- 3 different contact configurations
- Degree of protection IP67






PRODUCT DESCRIPTION

IDIS-1 is a small and very flexible key switch, suitable for smaller flaps. Thanks to the rotating head, it has eight key entry positions. The switch is available with a flat, angled or flexible wrench. The IDIS-1 switch has a standard spacing between the mounting holes - 22 mm. As long as the key is in the switch (cover closed), the circuit breaker safety contacts are closed.

TECHNICAL DATA

Actuator	Standard	
Annual usage	8 cycles per hour/24 hours per day/365 days	
Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508	
Conduit entry	M20	
Contacts	2NC 1NO	
Housing material	Polyester	
IP class	IP67	
Maximum approach / withdrawal speed	600 mm/s	
Mechanical reliability B10d	2.5 x 10 ^e operations at 100mA load	
Mounting	2 x M4	

MTTFd	356 years
PFHd	3.44 x 10 ⁻⁸
PL	e acc. ISO13849-1
Rated insulation voltage	600V ac
SIL	3 acc. EN62061
Thermal current (Ith)	5 A
Travel for positive opening	6 mm
Withstand voltage	2500V ac



Slow Make Break 3NC	Snap Action 1NC 1NO
€ 31 32	
⊕ 21 — 22	23 24
⊕ 11 — 12	⊕ 11 — 12
	⊕ 31——32 ⊕ 21——22