



IDEM GLM WIRE SWITCH

143064C

GLM M20 '2NC 2NO' LED 230V



- Up to 30 m on one switch
- 5 different contact configurations
- 2 - color LED
- Integrated emergency button



PRODUCT DESCRIPTION

The GLM wire switches in the aluminum alloy housing have been created as a high-quality system for securing short conveyors, with a range of up to 30 m per one switch. Using the two switches, the range increases to 50 m.

The 2-color LED, signaling the operation of the switch, is visible from a large distance. The GLM wire switch has 5 different contact configurations.

TECHNICAL DATA

Annual usage	8 cycles per hour/24 hours per day/365 days
Approvals	EN60947-5-5, ISO 13850, ISO 13849-1, EN62061, EN60947-5-1, UL 508, CE, cULus, TÜV
Conduit entry	3 x M20
Contact type	EN60947-5-1 double break type Zb. Snap action up to 4NC (positive break) 2NO (auxiliary)
Contacts	2NC 2NO
Fittings	LED
Housing material	Die cast metal
Integrated emergency stop button	No
Integrated LED indication	Yes

IP class	IP67
LED indication	Steady green/Flashing red
LED supply voltage	230Vac
Mechanical reliability B10d	1.5 x 10 ⁶ operations at 100mA load
Mounting	4 x M5
MTTFd	214 years
Operating temperature	-25°C +80°C
PFHd	<1.0 x 10 ⁻⁷
Rope span	Up to 50m (2 switches) 30m (1 switch)
Rope tension device	IDEM tensioner/gripper (quick fixing)
Rope type	4.00mm outside diameter. Steel inner - PVC sheath
Short circuit overload protection	Fuse externally 10A(FF)
Tension force (typical mid setting)	130 N
Termination	Clamp up to 2.5mm ² conductors
Thermal current (Ith)	10 A
Typical operating force (rope pulled)	<125N <300mm deflection
Weight	640 g

