SUCO - 0601/0602 PRESSURE SENSOR

Performance series

0601102411002 0-10V, 0..100 bar, G1/4-E, NBR, M12

- Measuring range up to 100 bar
- Ceramic sensor
- Small and compact
- · Stainless steel housing





PRODUCT DESCRIPTION

The SUCO 0601/0602 performance series pressure sensor is a small, compact and cost effective pressure monitoring solution. Offering six standard pressure ranges with options of four different electrical connectors a thread of G1/4 and 0-10V or 4-20mA outputs. The 06 series uses a ceramic sensor in thick film technology which is housed in a stainless steel body.

Common applications include mobile hydraulics and power packs.

TECHNICAL DATA

Accuracy	±1% FS
Burst pressure	300 bar
Connection	G1/4-E
Electrical connection	M12x1 4-pole
IP class	IP67
Long term stability	±0.3% FS p.a.
Material of body	Stainless steel 1.4305
Material of body Material of wetted parts	Stainless steel 1.4305 Stainless steel 1.4305, Ceramic, NBR
•	
Material of wetted parts	Stainless steel 1.4305, Ceramic, NBR
Material of wetted parts Mechanical life expectancy	Stainless steel 1.4305, Ceramic, NBR 5 million cycles
Material of wetted parts Mechanical life expectancy Overpressure protection	Stainless steel 1.4305, Ceramic, NBR 5 million cycles 200 bar

Pressure reference	Gauge
Pressure rise	1 bar/ms
Repeatability	±0.1% FS
Response time	2 ms
Shock resistance	"500m / s²; 11 ms half sine wave; DIN EN 60068-2-27"
Signal type	0-10 V
Supply voltage dc max	32 V DC
Supply voltage dc min	11 V DC
Temperature ambient from	-30 °C
Temperature ambient to	100 °C
Temperature error	±0.04% FS/°C
Temperature of media from	-30 °C
Temperature of media to	100 °C
Weight	80 g
Vibration resistance	20g: 42000 Hz sine wave, DIN EN 60068-2-6









AMP Superseal 1.5*		De	utsch DTO-	4-3P	
Pin	0601 U _M	0602 nc*	Pin A	0601 Uv+	060. Uve
2	Gnd	lac	8	Gnd	nc*
	Ure	Uve	C	Ume	L
3	IP67		IP67, IP6K9K		
3	IP67			IP67, IP6K9	k.
	IP67 x ~ 61 mm	,		x - 61 mm	