



PK 550

10247.1

PK 550/2/3,50-V GN



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Type	PCB terminal
Pitch	3,5 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

RATINGS

Rated current	13,5 A
Rated voltage	130 V
Rated cross section	1 mm ²
Rated impulse voltage	1,25 kV
Overvoltage category	III
Contamination degree	3

DIMENSIONS

Length	6,5 mm
Width	7 mm
Height	8,2 mm
Width left	1,75 mm
Width right	1,75 mm
Drillhole diameter	1,2 mm

Diameter of the connection pin	0,9 mm
Length of pin	3,5 mm

CONNECTION DATA

Connector type/principle	Wire protection
Number of levels	1
Angle of PCB/wire connection	0°/180° (horizontal)
Type of attachment to PCB	Connecting contact
Electrical connection type to PCB	Solder
Cross section single wire from	0,08 mm ²
Cross section single wire to	1,5 mm ²
Cross section stranded wire from	0,08 mm ²
Cross section stranded with ferrule to	0,5 mm ²
Cross section stranded wire to	1 mm ²
Cross section stranded with ferrule from	0,14 mm ²
Rated wire cross section to (AWG)	16
Rated wire cross section from (AWG)	28
Stripping length	5,5 mm
Screw size	M 2
Torque	0,2 Nm

MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Screw material	Steel
Clamp material	Brass
Wire protection	Stainless steel

APPROVALS

UL test standard	UL 1059
Rated voltage UL	125 V
Rated current UL	6 A
cUL test standard	CSA 22.2 No.158
Rated voltage cUL	125 V

