## VARIOLINE LAMP WITH SOCKET LED 121/122 - OBSOLETE - NEW RANGE COMING SOON

Varioline

12203.0-00 OBSOLETE - LED 122 220-240 V AC, on/off switch, screw fixing,UK/Ireland socket

• OBSOLETE

- FOR LED LIGHT USE LED 025
- FOR SOCKETS USE SD 035





#### PRODUCT DESCRIPTION

LED 121/122 Range is now Obsolete - Stego has a New Range coming Mid 2024

# **TECHNICAL DATA**

#### **GENERAL DATA**

| Mounting               | Screw fixing               |
|------------------------|----------------------------|
| Nominal voltage        | 220-240 V AC               |
| Activation             | Switch                     |
| Connection type        | 3-pole plug with snap lock |
| Socket                 | UK/IE                      |
| Nominal socket current | 13 A                       |
| Light source           | LED                        |
| Luminance              | 1.080 Lm/1.730 Lm          |
| Life span              | 60,000h at +20°C           |
| DIMENSIONS             |                            |
| Length                 | 700 mm                     |

| Length | 700 mm |
|--------|--------|
| Width  | 100 mm |
| Height | 44 mm  |

# **ELECTRICAL SPECIFICATION**

| Frequency         | 50/60 Hz |
|-------------------|----------|
| Power consumption | 16 W     |

## **SAFETY & APPROVALS**


| Protection class  | I (earthed) |
|-------------------|-------------|
| IP class          | IP20        |
| Approvals         | CE, RoHS    |
| Approvals pending | VDE         |

#### **MATERIALS - CONDITIONS**


| Material of body        | Plastic           |
|-------------------------|-------------------|
| Colour                  | Translucent/White |
| Operational temperature | -30°C +40°C       |
| Storage temperature     | -40°C +85°C       |
| Operating humidity      | < 90% RH          |
| Humidity storage        | <90% RH           |
|                         |                   |


## **ADDITIONAL DATA**

| Weight      | 0,4 kg   |
|-------------|----------|
| Voltage max | 265 V ac |
| Voltage min | 200 V ac |



L2 = 475 mm





View of screw fixing



