VARIOLINE LAMP WITH SOCKET LED 121/122 - OBSOLETE - NEW RANGE COMING SOON

Varioline

12224.0-00 OBSOLETE - LED 122 120V AC, door switch, screw fixing, USA/Canada socket

- OBSOLETE
- FOR LED LIGHT USE LED 025
- FOR SOCKETS USE SD 035





PRODUCT DESCRIPTION

LED 121/122 Range is now Obsolete - Stego has a New Range coming Mid 2024

TECHNICAL DATA

GENERAL DATA

| Mounting | Screw fixing |
|------------------------|----------------------------|
| Nominal voltage | 120 V AC |
| Activation | Door switch |
| Connection type | 3-pole plug with snap lock |
| Socket | USA/CA |
| Nominal socket current | 15 A |
| Light source | LED |
| Luminance | 1.080 Lm/1.730 Lm |
| Life span | 60,000h at +20°C |
| | |

DIMENSIONS

| Length | 700 mm |
|--------|--------|
| Width | 100 mm |
| Height | 44 mm |

ELECTRICAL SPECIFICATION

| Frequency | 50/60 Hz |
|-------------------|----------|
| Power consumption | 16 W |

SAFETY & APPROVALS


| Protection class | I (earthed) |
|-------------------|-------------|
| IP class | IP20 |
| Approvals | CE, RoHS |
| Approvals pending | UL |

MATERIALS - CONDITIONS

| Material of body | Plastic |
|-------------------------|-------------------|
| Colour | Translucent/White |
| Operational temperature | -30°C +40°C |
| Storage temperature | -40°C +85°C |
| Operating humidity | < 90% RH |
| Humidity storage | <90% RH |

ADDITIONAL DATA

| Weight | 0,4 kg |
|-------------|----------|
| Voltage max | 130 V ac |
| Voltage min | 110 V ac |



L1 = 500 mm L2 = 475 mm L1 = 700 mm L2 = 675 mm

