VARIOLINE LAMP WITH SOCKET LED 121/122 - OBSOLETE - NEW RANGE COMING SOON

Varioline

12134.0-30 OBSOLETE - LED 121 120V AC, without switch, magnet fixing, USA/Canada socket

- OBSOLETE
- FOR LED LIGHT USE LED 025
- FOR SOCKETS USE SD 035





PRODUCT DESCRIPTION

LED 121/122 Range is now Obsolete - Stego has a New Range coming Mid 2024

TECHNICAL DATA

GENERAL DATA

| Mounting | Magnetic mount |
|------------------------|----------------------------|
| Nominal voltage | 120 V AC |
| Activation | No switch |
| Connection type | 3-pole plug with snap lock |
| Socket | USA/CA |
| Nominal socket current | 15 A |
| Light source | LED |
| Luminance | 1.080 Lm/1.730 Lm |
| Life span | 60,000h at +20°C |
| | |

DIMENSIONS

| Length | 500 mm |
|--------|--------|
| Width | 100 mm |
| Height | 44 mm |

ELECTRICAL SPECIFICATION

| Frequency | 50/60 Hz |
|-------------------|----------|
| Power consumption | 11 W |

SAFETY & APPROVALS


| Protection class | I (earthed) |
|-------------------|-------------|
| IP class | IP20 |
| Approvals | CE, RoHS |
| Approvals pending | UL |


MATERIALS - CONDITIONS


| Material of body | Plastic |
|-------------------------|-------------------|
| Colour | Translucent/White |
| Operational temperature | -30°C +40°C |
| Storage temperature | -40°C +85°C |
| Operating humidity | < 90% RH |
| Humidity storage | <90% RH |

ADDITIONAL DATA

| Weight | 0,4 kg |
|-------------|----------|
| Voltage max | 130 V ac |
| Voltage min | 110 V ac |







LED 121 (Size 1) L1 = 500 mm L2 = 475 mm LED 122 (Size 2) L1 = 700 mm L2 = 675 mm

