

## CROUZET SYR-LINE PLUG IN TIMER 8 PIN

Syr-Line Series

OL1R10MV1

SyrLine Recycle 10A 12-240Vac/dc 8pin

- Single or Multi-Function
- Multi time range 0.5 sec - 10 days
- Universal supply voltage 12-240Vac/dc
- 1 or 2 x 10A rated relay contacts



### PRODUCT DESCRIPTION

SyrLine, the new specialised range from Crouzet. Aimed to satisfy the most unique requirements of any application by innovations in design, engineering and development.

The new family of 8 pin plug-in analog timers - multifunction or monofunction, with a wide time range, and with all the classic timing functions.

## TECHNICAL DATA

### FUNCTION

|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| Function          | L, Li                                                             |
| Time range        | 0,5-10s, 0,05-1min, 0,5-10min, 0,05-1h, 0,5-10h, 0,05-1d, 0,5-10d |
| Close delay       | 40 ms                                                             |
| Response time off | 120 ms                                                            |
| Repeatability     | 0,5 %                                                             |
| Multi-function    | No                                                                |
| Output            | Relay 1 pole C/O                                                  |

### ELECTRICAL DATA

|                       |                                             |
|-----------------------|---------------------------------------------|
| Power consumption     | 1,5 W                                       |
| Breaking capacity     | 2500 VA / 300W                              |
| Switching current max | 10 A                                        |
| Electrical lifetime   | 105 cycles min at 10A 250V (resistive load) |

|                                   |                           |
|-----------------------------------|---------------------------|
| <b>Mechanical life expectancy</b> | 10x10 <sup>6</sup> cycles |
| <b>Supply voltage</b>             | 12-240V AC/DC             |

### OTHER TECHNICAL DATA

|                                    |                        |
|------------------------------------|------------------------|
| <b>Mounting</b>                    | 8-pin socket           |
| <b>Temperature operational min</b> | -20 °C                 |
| <b>Temperature operational max</b> | 60 °C                  |
| <b>Storage temperature min</b>     | -40 °C                 |
| <b>Storage temperature max</b>     | 70 °C                  |
| <b>Approvals</b>                   | CE, cULus, REACH, RoHS |
| <b>Width</b>                       | 35 mm                  |
| <b>Depth</b>                       | 95,6 mm                |
| <b>Height</b>                      | 53 mm                  |
| <b>IP class</b>                    | IP40                   |

Function L - Recycler (OFF Start)



Function Li - Recycler (ON Start)

