




COMING SOON

PRK, PSL, PRKD, PIKD

27030.5

PRK 16/2A Blue, 16mm² Push-in feed through

- 1.5mm Double & Triple Deck
- 16mm feed through



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Rated wire cross section	16 mm ²
Colour	Blue
Rated voltage IEC	1000 V
Rated current IEC	85 A
Mounting	Mounting rail TS 35/7.5
Rated impulse voltage	8 kV
Overvoltage category	III
Contamination degree	3

DIMENSIONS

Length	75 mm
Width	12,1 mm
Height TS 35/7.5	49,5 mm
Height	48 mm

CONNECTION DATA

Connections	2
Number of levels	1
Plug gauge acc. EN 60 947-1	A7
Cross connect channels	2
Cross section single wire from	0,5 mm ²
Cross section single wire to	25 mm ²
Cross section stranded wire from	0,5 mm ²
Cross section stranded wire to	16 mm ²
Cross section stranded with ferrule from	0,5 mm ²
Cross section stranded with ferrule to	16 mm ²
Rated wire cross section from	20 AWG
Rated wire cross section to	4 AWG
Stripping length	18 mm

MATERIALS

Insulation material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-40 °C
Operating temperature to	120 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	1 g
Pack size	50
Number of terminals per level	2