



TECNOPLASTIC FLOAT SWITCH TAURUS-DRINK

GTAA3X110BB01

Taurus-Drink, ACS 3X1, 10M, 2 func.

- Internal counterweight
- 20 metres maximum depth
- Up to 40°C
- Three chamber design
- Suitable for use in drinking water



PRODUCT DESCRIPTION

Unlike traditional floats that float on the water's surface, the Taurus level switch, thanks to its special construction of an integrated counterweight, remains under water.

The Taurus has three watertight chambers meaning it is very robust and reliable in critical applications.

Used alone or in multiples, minimum and maximum levels/high and low alarm outputs can be maintained and adjusted easily.

Manufactured from non-toxic material suitable for food industry and intended for permanent usage in potable water.

- Water mains
- Drinking water fountains
- Drinks and foodstuffs
- Aquarium
- Fish farms
- Swimming pool

TECHNICAL DATA

Activation angle	20 °
Approvals	ACS, CE
Cable length	10 m
Cable type	ACS + AD8 3X1
Depth max	20 m
Fixing kit included	Yes
Insulation class	II
IP class	IP68
Material of float	Polypropylene
Operating temperature to	40 °C
Rated current	8 A

Specific gravity	0.95 - 1.05kg/dm ³
Supply voltage	250 V