

DATALOGIC POWERSCAN PBT/PM9100

PBT9100-RBK20EU

PowerScan PBT9100, Removable batt, RS-232 kit EU,
(Base,cable,power)

- Detects 1D code types
- Reads up to 2.5 mils codes
- 60,000+ reads per charge
- Interfaces: keyboard wedge, RS-232, USB



PRODUCT DESCRIPTION

TECHNICAL DATA

1D Code types	Code 39, Code 93, Code 128, EAN128, Codabar, Plessey, Code 32, Code 11, MSI, GS1 DataBar linear codes, IATA, Follet 2/5, Code 4, Code 5, Codablock F, UPC/EAN, UPC/EAN P2/P5 add ons, UPC/EAN Coupons, ISBN, Code 39 Full ASCII, Interleaved 2/5, Standard 2/5, Code 39 CIP, Industrial 2/5, Datalogic 2/5
Additional features	Kit includes: Scanner PBT9100-RB, Base BC9030-BT, Cable CAB-433, Power Adapter 8-0935, Power Cord 6003-0940
Approvals	RoHS
Battery	Lithium-ion 3350 mA
Charge time	4.5 hrs
Colour	Black, Yellow
Dimension (mm)	212 x 110 x 74
Drop resistance	Withstands 50 drops from 6.6ft onto concrete surface
Humidity	0-95% (Non-condensing)
Interface	Keyboard wedge, RS-232, USB
IP class	IP65
Kit	Yes
Light source	Green LED

Readable code types	1D / Linear Codes
Reading angle window	Pitch: +/-75°; Tilt: +/- 45°; Skew: +/-70°
Reads per charge	60000
Resolution	2.5 mils
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	50 °C
Temperature operational min	-20 °C
Weight	405 g
Wireless	Yes
Wireless technology	Bluetooth Wireless Technology