

DATALOGIC - S3N - MINIATURE SENSOR

S3N-PR-5-FG01-NL
Through Beam Light Output NPN M8 Connector















- High performance miniature sensor
- Universal 25.4mm mounting holes
- Embedded cable or M8 connector
- Light-on/Dark on selectable models available
- PNP or NPN output



PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE, UL
Distance max	20000 mm
Distance min	0 mm
Electrical connection	M8 4-pole connector
Function	light on
IP class	IP67
Lens material	PMMA
Light type	Red LED
Material protection	PMMA
Output	NPN
Photocell technology	Transmitter / receiver
Storage temperature max	70 °C
Storage temperature min	-25 °C
Supply voltage	10-30 V DC
Temperature operational max	55 °C
Temperature operational min	-25 °C



S3N Front view	Model	A	B
	S3N-P1-6-1111-11	7.2	8.25
	S3N-P1-6-1111-02	7.2	8.2
	S3N-P1-3-1111-11	7.2	10.65
	S3N-P1-3-1111-02	7.2	6.3
	S3N-P1-6-1111-11	7.2	7
	S3N-P1-6-1111-02	7.2	10.2
	S3N-P1-3-1111-11	7.2	13.6
	S3N-P1-3-1111-02	7.2	13.8
	S3N-P1-6-1111-11	7.2	7.5
	S3N-P1-6-1111-02	7.2	7.5