





Overall dimensions for vertical mounting using recommended mating connector and retainer



Overall dimensions for horizontal mounting

Features

- Motor supply: 9-36V. Optional logic supply: 7-36V
- Output current: 4A cont. (BLDC mode); 10A_{PEAK}, up to 100KHz PWM
- Digital Hall sensor interface (single-ended and open collector)
- Incremental encoder interface (single-ended, open collector and differential)
- Linear Hall sensors interface
- Analogue sin/cos encoder interface (differential 1V_{pp})
- 5 digital inputs, 5-36V, NPN: Enable, 2 for limit switches, general-purpose 2
- 4 digital outputs, 5-36V, 0.5A, NPN O.C.: Ready, Error, 2 general-purpose
- 2 analogue inputs: 12-bit, 0-5V: Reference, Feedback or general purpose
- RS-232 serial & CAN-bus 2.0B interfaces with h/w selectable addresses
- TMLCAN and CANopen (CiA 301v4.2 and 402v3.0) protocols
- 1K × 16 SRAM for data acquisition
- 4K × 16 E²ROM to store TML motion programs and data
- Operating ambient temperature: 0-40°C (over 40°C with derating)
- Hardware Protections: short-circuit between motor phases and from motor phases to GND, over-voltage, under-voltage and I²t

Motor – sensor configurations

Sensor \ Motor	PMSM	BLDC	DC BRUSH	STEP (2-ph)	STEP (3-ph)
Incr. Encoder	Y		Y	Y	
Incr. Encoder + Hall	Y	Y			
Analog Sin/Cos encoder	Y				
Linear Halls	Y				
Tacho			Y		
Open-loop (no sensor)				Y	Y

NOTE:

SSI, EnDAT, BiSS encoders and Resolver feedback is possible with an additional feedback extension module

Mating Connector

Producer	Part No.	Description
Tyco	2-1775801-4	PCIe 4x vertical card edge connector, 1.0mm pitch, 2x32 contacts
FCI	10018784-11101TLF	
Tyco	1761465-2	PCIe 4x horizontal card edge connector, 1.0mm pitch, 2x32 contacts
Samtec	PCIE-064-02-F-D-RA	
FCI	10035591-001LF	Retainer for vertical PCIe card
FCI	10042618-002LF	

Connector description

Pin	Name	Type	Description
A1	GND	-	Return ground for extension bus
A2	reserved	I/O	Reserved, do not connect
A3	reserved	O	Reserved, do not connect
A4	reserved	I/O	Reserved, do not connect
A5	reserved	I/O	Reserved, do not connect
A6	OUT1 [†]	O	5-36V 0.5A digital output, NPN O.C. / TTL pull-up
A7	reserved	I/O	Reserved, do not connect
A8	Hall 1	I	Digital input Hall 1 sensor
A9	Hall 2	I	Digital input Hall 2 sensor
A10	Hall 3	I	Digital input Hall 3 sensor
A11	+5V _{OUT}	O	5V supply for sensors - internally generated
A12	GND	-	Return ground for sensors supply
A13	A- /Sin-/LH1	I	Incr. encoder A- diff. input, or analogue encoder Sin- diff. input, or linear Hall 1 input
A14	A/A+/Sin+	I	Incr. encoder A single-ended, or A+ diff. input, or analogue encoder Sin+ diff. input
A15	B-/Cos-/LH2	I	Incr. encoder B- diff. input, or analogue encoder Cos- diff. input, or linear Hall 2 input

Name A. N.	First edition September 13, 2011	Document template: P099.TQT.564.0001	Last edition September 10, 2013	Visa : R. G.
 TECHNOSOFT		iPOS3604 VX-CAN PRODUCT DATA SHEET		P028.002.E001.DSH.10F.docx Page: 1 of 5

J1	A16	B/B+/Cos+	I	Incr. encoder B single-ended, or B+ diff. input, or analogue encoder Cos+ diff. input
	A17	Z- /LH3	I	Incr. encoder Z- diff. input, or linear Hall 3 input
	A18	Z/ Z+	I	Incr. encoder Z (index) single-ended, or Z+ diff. input
	A19	Can-Hi	I/O	CAN-Bus positive line (dominant high)
	A20	GND	-	Negative return (ground) of the logic supply
	A21,22	+V _{MOT}	I	Positive terminal of the motor supply: 9 to 36V _{DC}
	A23,24	GND	-	Negative return (ground) of the motor supply
	A25-28	BR/B-	O	Brake resistor / Phase B- for step motors
	A29-32	B/A-	O	Phase B for 3-ph motors, A- for 2-ph steppers, Motor- for DC brush motors

	Pin	Name	Type	Description
J1	B1	GND	-	Return ground for CAN-Bus and RS-232 pins
	B2	232TX	O	RS-232 Data Transmission
	B3	232RX	I	RS-232 Data Reception
	B4	OUT0	O	5-36V 0.5A general-purpose digital output, NPN open-collector / TTL pull-up
	B5	GND	-	Return ground for I/O pins
	B6	AxisID 0	I	Axis ID/Address input. 7 states: floating, strap to GND or +5V, resistor 4K7 or 22K to GND or +5V
	B7	AxisID 1	I	Axis ID/Address input. 7 states: floating, strap to GND or +5V, resistor 4K7 or 22K to GND or +5V
	B8	AxisID 2	I	Axis ID/Address input. 7 states: floating, strap to GND or +5V, resistor 4K7 or 22K to GND or +5V
	B9	REF	I	Analogue input, 12-bit, 0-5V. Used to read an analog position, speed or torque reference, or used as general purpose analogue input
	B10	FDBK	I	Analogue input, 12-bit, 0-5V. Used to read an analogue position or speed feedback (as tach), or used as general purpose analogue input
	B11	+5V _{OUT}	O	5V output supply for I/O usage
	B12	OUT2/Error	O	5-36V 0.5A drive error output, active low, NPN open-collector/TTL pull-up. Also drives the red LED
	B13	OUT3/Ready	O	5-36V 0.5A drive ready output, active low, NPN open-collector/TTL pull-up. Also drives the green LED.
	B14	IN0	I	5-36V digital input General-purpose
	B15	IN1	I	5-36V digital input
	B16	IN2/LSP	I	5-36V digital input Positive limit switch input
	B17	IN3/LSN	I	5-36V digital input. Negative limit switch input
	B18	IN4/Enable	I	5-36V digital input. Drive enable input
	B19	Can-Lo	I/O	CAN-Bus negative line (dominant low)
	B20	+V _{LOG}	I	Positive terminal of the logic supply: 7 to 36V _{DC}
	B21, 22	+V _{MOT}	I	Positive terminal of the motor supply: 9 to 36V _{DC}
	B23,24	GND	-	Negative return (ground) of the motor supply
	B25-28	C/B+	O	Phase C for 3-ph motors, B+ for 2-ph steppers
	B29-32	A/A+	O	Phase A for 3-ph motors, A+ for 2-ph steppers. Motor+ for DC brush motors

† not available when additional feedback extension module is used

Electrical characteristics

All parameters measured under the following conditions (unless otherwise specified):

- Tamb = 0...40°C, VLOG = 24 VDC; VMOT = 36VDC
- Supplies start-up / shutdown sequence: -any-
- Load current (sinusoidal amplitude / continuous BLDC, DC, stepper) = 4A

Operating Conditions		Min.	Typ.	Max.	Units
Ambient temperature ¹		0		+40	°C
	Ambient humidity	0		90	%Rh
	Altitude / pressure ²	-0.1	0 ÷ 2.5	10.0	Km
Altitude / pressure ²	Altitude (vs. sea level)	-0.1	0 ÷ 2.5	10.0	Km
	Ambient Pressure	0	0.75 ÷ 1	10.0	atm
Storage Conditions		Min.	Typ.	Max.	Units
Ambient temperature		-40		+85	°C
Ambient humidity		0		100	%Rh
Ambient Pressure		0		10.0	atm
ESD capability (Human body model)	Not powered; applies to any accessible part			±0.5	kV
	Original packaging			±15	kV
Mechanical Mounting		Min.	Typ.	Max.	Units
Airflow		natural convection ³ , closed box			
Spacing required for vertical mounting	Between adjacent drives	30			mm
	Between drives and nearby walls	30			mm
	Between drives and roof-top	20			mm
Spacing required for horizontal mounting	Between adjacent drives	4			mm
	Between drives and nearby walls	5			mm
	Space needed for drive removal	10			mm
	Between drives and roof-top	15			mm
Insertion force	Using recommended mating connectors; without retainer		20	36	N
	Extraction force	5	10		N
Environmental Characteristics		Min.	Typ.	Max.	Units
Size (Length x Width x Height)	Without mating connector / retainer	56 x 28.8 x 7.6			mm
	With recommended mating vertical connector and retainer. Height above PCB surface.	~2.2 x 1.1 x 0.3			inch
	With recommended mating horizontal connector. Height above PCB surface.	63.3 x 32.6 x 16.3			mm
	With recommended mating horizontal connector. Height above PCB surface.	~2.5 x 1.3 x 0.64			inch
	With recommended mating horizontal connector. Height above PCB surface.	56 x 41.2 x 7.6			mm
Weight		10			g
Power dissipation	Idle (no load)		1		W
	Operating		3		W
Efficiency			98		%
Cleaning agents		Dry cleaning is recommended Only Water- or Alcohol- based			
Protection degree		According to IEC60529, UL508 IP00			-
Logic Supply Input (+V _{LOG})		Min.	Typ.	Max.	Units
Supply voltage	Nominal values	7		36	V _{DC}
	Absolute maximum values, drive operating but outside guaranteed parameters	4.9		40	V _{DC}
	Absolute maximum values, continuous	-0.7		42	V _{DC}
	Absolute maximum values, surge (duration ≤ 10ms) †	-1		+45	V
Supply current	+V _{LOG} = 7V		125	300	mA
	+V _{LOG} = 12V		80	200	
	+V _{LOG} = 24V		50	125	
	+V _{LOG} = 40V		40	100	
Motor Supply Input (+V _{MOT})		Min.	Typ.	Max.	Units
Supply voltage	Nominal values	9		36	V _{DC}
	Absolute maximum values, drive operating but outside guaranteed parameters	8.5		40	V _{DC}
	Absolute maximum values, continuous	-0.7		42	V _{DC}
	Absolute maximum values, surge (duration ≤ 10ms) †	-1		+45	V
Supply current			1	5	mA

¹ Operating temperature can be extended up to +65°C with reduced current and power ratings.

² iPOS360x can be operated in vacuum (no altitude restriction), but at altitudes over 2,500m, current and power rating are reduced due to thermal dissipation efficiency.

³ In case of forced cooling (conduction or ventilation) the spacing requirements may drop substantially down to zero as long as the ambient temperature is kept below the maximum operating limit

Name A. N.	First edition September 13, 2011	Document template: P099.TQT.564.0001	Last edition September 10, 2013	Visa : R. G.
 TECHNOSOFT		Title of document iPOS3604 VX-CAN PRODUCT DATA SHEET	N° document P028.002.E001.DSH.10F.docx Page: 2 of 5	

Supply current	Operating		-10	±4	+10	A
	Absolute maximum value, short-circuit condition (duration ≤ 10ms) [†]				15	A
Motor Outputs (A/A+, B/A-, C/B+, BR/B-)			Min.	Typ.	Max.	Units
Nominal output current, continuous	for DC brushed, steppers and BLDC motors with Hall-based trapezoidal control				4	A
	for PMSM motors with FOC sinusoidal control (sinusoidal amplitude value)				4	
	for PMSM motors with FOC sinusoidal control (sinusoidal effective value)				2.82	
Motor output current, peak	maximum 2.5s		-10		+10	A
Short-circuit protection threshold	measurement range			±13	±15	A
Short-circuit protection delay			5	10		μS
On-state voltage drop	Nominal output current; including typical mating connector contact resistance			±0.3	±0.5	V
Off-state leakage current				±0.5	±1	mA
Motor inductance (phase-to-phase)	Recommended value, for current ripple max. ±5% of full range; +V _{MOT} = 36 V	F _{PWM}				μH
		20 kHz	250			
		40 kHz	120			
		60 kHz	100			
		80 kHz	60			
		100 kHz	45			
	Minimum value, limited by short-circuit protection; +V _{MOT} = 36 V	20 kHz	75			μH
		40 kHz	25			
		60 kHz	20			
		80 kHz	10			
		100 kHz	5			
Motor electrical time-constant (L/R)	Recommended value for ±5% current measurement error	20 kHz	250			μs
		40 kHz	125			
		60 kHz	100			
		80 kHz	63			
		100 kHz	50			
Current measurement	FS = Full Scale accuracy			±4	±8	%FS
Digital Inputs (IN0, IN1, IN2/LSP, IN3/LSN, IN4/Enable)			Min.	Typ.	Max.	Units
Mode compliance			TTL / CMOS / LVTTTL (3.3V) / Open-collector / NPN / 24V outputs			
Default state	Input floating (wiring disconnected)		Logic HIGH			
Input voltage	Logic "LOW"			0	0.8	V
	Logic "HIGH"		2	5÷24		
	Floating voltage (not connected)			3		
	Absolute maximum, continuous		-10		+30	
	Absolute maximum, surge (duration ≤ 1S) [†]		-20		+40	
Input current	Logic "LOW"; ulled to GND			0.6	1	mA
	Logic "HIGH"; Internal 4.7KΩ pull-up to +3.3		0	0	0	
	Logic "HIGH"; Pulled to +5V			0.15	0.2	
	Logic "HIGH"; Pulled to +24V			2	2.5	
Input frequency			0		150	KHz
Minimum pulse			3.3			μS
ESD protection	Human body model		±5			KV
Digital Outputs (OUT0, OUT1, OUT2/Error, OUT3/ Ready)			Min.	Typ.	Max.	Units
Mode compliance	All outputs (OUT0, OUT1, OUT2/Error, OUT3/Ready)		TTL / CMOS / Open-collector / NPN 24V			
	Ready, Error		Same as above + LVTTTL (3.3V)			
Default state	Not supplied (+V _{LOG} floating or to GND)		High-Z (floating)			
	Immediately after power-up	OUT0, OUT1	Logic "HIGH"			
		OUT2/Error, OUT3/ Ready	Logic "LOW"			
	Normal operation		OUT0, OUT1, OUT2/Error	Logic "HIGH"		
OUT3/Ready			Logic "LOW"			


Output voltage	Logic "LOW"; output current = 0.5A			0.2	0.8	V
	Logic "HIGH"; output current = 0, no load	OUT2/Error, OUT3/ Ready	2.9	3	3.3	
		OUT0, OUT1	4	4.5	5	
	Logic "HIGH", external load to +V _{LOG}			V _{LOG}		
	Absolute maximum, continuous		-0.5		V _{LOG} +0.5	
	Absolute maximum, surge (duration ≤ 1S) †		-1		V _{LOG} +1	
Output current	Logic "LOW", sink current, continuous				0.5	A
	Logic "LOW", sink current, pulse ≤ 5 sec.				1	A
	Logic "HIGH", source current; external load to GND; V _{OUT} ≥ 2.0V	OUT2/Error , OUT3/ Ready			2	mA
		OUT0, OUT1			4	mA
	Logic "HIGH", leakage current; external load to +V _{LOG} ; V _{OUT} = V _{LOG} max = 40V			0.1	0.2	mA
Minimum pulse width			2			μS
ESD protection	Human body model		±5			KV
Digital Hall Inputs (Hall1, Hall2, Hall3)			Min.	Typ.	Max.	Units
Mode compliance			TTL / CMOS / Open-collector			
Default state	Input floating (wiring disconnected)		Logic HIGH			
Input voltage	Logic "LOW"			0	0.8	V
	Logic "HIGH"		2	5		
	Floating voltage (not connected)			4.4		
	Absolute maximum, surge (duration ≤ 1S) †		-10		+15	
Input current	Logic "LOW"; Pull to GND				1.2	mA
	Logic "HIGH"; Internal 4.7KΩ pull-up to +5		0	0	0	
Minimum pulse width			2			μS
ESD protection	Human body model		±5			KV
Encoder Inputs (A/A+, A-, B/B+, B-, Z/Z+, Z)			Min.	Typ.	Max.	Units
Single-ended mode compliance	Leave negative inputs disconnected		TTL / CMOS / Open-collector			
Input voltage, single-ended mode A/A+, B/B+	Logic "LOW"				1.6	V
	Logic "HIGH"		1.8			
	Floating voltage (not connected)			4.5		
Input voltage, single-ended mode Z/Z+	Logic "LOW"				1.2	V
	Logic "HIGH"		1.4			
	Floating voltage (not connected)			4.7		
Input current, single-ended mode A/A+, B/B+, Z/Z+	Logic "LOW"; Pull to GND			2.5	3	mA
	Logic "HIGH"; Internal 2.2KΩ pull-up to +5		0	0	0	
Differential mode compliance	For full RS422 compliance, see 1		TIA/EIA-422-A			
Input voltage, differential mode	Hysteresis		±0.06	±0.1	±0.2	V
	Common-mode range (A+ to GND, etc.)		-7		+7	
Input impedance, differential	A+ to A-, B+ to B-		4.2	4.7		KΩ
	Z+ to Z-		6.1	7.2		
Input frequency	Single-ended mode, Open-collector / NPN		0		500	KHz
	Differential mode, or Single-ended driven by push-pull (TTL / CMOS)		0		10	MHz
Minimum pulse width	Single-ended mode, Open-collector / NPN		1			μS
	Differential mode, or Single-ended driven by push-pull (TTL / CMOS)		50			nS
Input voltage, any pin to GND	Absolute maximum values, continuous		-7		+7	V

¹ For full RS-422 compliance, 120Ω termination resistors must be connected across the differential pairs, as close as possible to the drive input pins.


Name	First edition	Document template: P099.TQT.564.0001		Last edition	Visa :
A. N.	September 13, 2011			September 10, 2013	R. G.
 TECHNOSOFT		Title of document		N° document	
		iPOS3604 VX-CAN PRODUCT DATA SHEET		P028.002.E001.DSH.10F.docx Page: 3 of 5	

Input voltage, any pin to GND	Absolute maximum, surge (duration ≤ 1S) †	-11		+14	V
ESD protection	Human body model	±1			KV
Linear Hall Inputs (LH1, LH2, LH3)		Min.	Typ.	Max.	Units
Input voltage	Operational range	0	0.5÷4.5	4.9	V
Input voltage	Absolute maximum values, continuous	-7		+7	V
	Absolute maximum, surge (duration ≤ 1S) †	-11		+14	
Input current	Input voltage 0...+5V	-1	±0.9	+1	mA
Interpolation Resolution	Depending on software settings			11	bits
Frequency		0		1	KHz
ESD protection	Human body model	±1			KV
Sin-Cos Encoder Inputs (Sin+, Sin-, Cos+, Cos-)		Min.	Typ.	Max.	Units
Input voltage, differential	Sin+ to Sin-, Cos+ to Cos-		1	1.25	V _{PP}
Input voltage, any pin to GND	Operational range	-1	2.5	4	V
	Absolute maximum values, continuous	-7		+7	
	Absolute maximum, surge (duration ≤ 1S) †	-11		+14	
Input impedance	Differential, Sin+ to Sin-, Cos+ to Cos- ¹	4.2	4.7		KΩ
	Common-mode, to GND		2.2		KΩ
Resolution with interpolation	Software selectable, for one sine/cosine period	2		10	bits
Frequency	Sin-Cos interpolation	0		450	KHz
	Quadrature, no interpolation	0		10	MHz
ESD protection	Human body model	±1			KV
Analog 0...5V Inputs (REF, FDBK)		Min.	Typ.	Max.	Units
Input voltage	Operational range	0		4.95	V
	Absolute maximum values, continuous	-12		+18	
	Absolute maximum, surge (duration ≤ 1S) †			±36	
	To GND		30		
Input impedance			12		KΩ
Resolution					bits
Integral linearity				±2	bits
Offset error			±2	±10	bits
Gain error			±1%	±3%	% FS ²
Bandwidth (-3dB)	Software selectable	0		1	KHz
ESD protection	Human body model	±5			KV
Axis ID Inputs (AxisID 0, AxisID 1, AxisID 2)		Min.	Typ.	Max.	Units
External connections	7 levels	Not connected; Strap to GND; Strap to +5V; 4.7KΩ to GND; 4.7KΩ to +5V; 22KΩ to GND; 22KΩ to +5V;			
Pin current	Use to size PCB tracks			±0.5	mA
4.7KΩ/22KΩ resistor	Power rating	3			mW
	Tolerance			±5	%
ESD protection	Human body model	±5			KV
RS-232		Min.	Typ.	Max.	Units
Compliance		TIA/EIA-232-C			
Bit rate	Software selectable	9600		115200	Baud
Short-circuit	232TX short to GND	Guaranteed			
ESD protection	Human body model	±2			KV
CAN-Bus		Min.	Typ.	Max.	Units
Compliance		ISO11898, CiA-301v4.2 & 402v3.0			
Bit rate	Software selectable	125		1000	Kbps
Bus length	1Mbps			25	m
	800Kbps			50	
	500Kbps			100	
	≤ 250Kbps			250	
Resistor	Between CAN-Hi, CAN-Lo	none on-board			
Node addressing	Strapping option (AxisID0,1,2)	1 ÷ 127 (CANopen); 1-195 & 255 (TLMCAN)			
ESD protection	Human body model	±15			KV
Supply Output (+5V)		Min.	Typ.	Max.	Units
Output voltage	Current sourced = 250mA	4.8	5	5.2	V
Output current		250	350		mA
Short-circuit		NOT protected			
Over-voltage		NOT protected			
ESD protection	Human body model	±1			KV


† Stresses beyond values listed under "absolute maximum ratings" may cause permanent damage to the device. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.




De-rating with ambient temperature



De-rating with altitude




Current De-rating with PWM frequency



Over-current diagram

¹ For many applications, an 120Ω termination resistor should be connected across Sin+ to Sin-, and ² "FS" stands for "Full Scale" across COS+ to COS-. Please consult the feedback device datasheet for confirmation.

Name A. N.	First edition September 13, 2011	Document template: P099.TQT.564.0001	Last edition September 10, 2013	Visa : R. G.
 TECHNOSOFT		Title of document iPOS3604 VX-CAN PRODUCT DATA SHEET	N° document P028.002.E001.DSH.10F.docx Page: 4 of 5	



Output Voltage De-rating with PWM frequency¹

¹ V_{OUT} – the output voltage, V_{MOT} – the motor supply voltage

Name A. N.	First edition September 13, 2011	Document template: P099.TQT.564.0001	Last edition September 10, 2013	Visa : R. G.
 TECHNOSOFT		Title of document iPOS3604 VX-CAN PRODUCT DATA SHEET	N° document P028.002.E001.DSH.10F.docx Page: 5 of 5	