


iPOS360x BX-CAN connectors and pinout









Compatible products		
Part No.	Name	Description
P028.001.E201	iPOS3602 BX-CAN	Standard execution, differential encoder
P028.001.E601		Single ended encoder execution
P028.001.E701		Linear Halls execution
P028.002.E201	iPOS3604 BX-CAN	Standard execution, differential encoder
P028.002.E601		Single ended encoder execution
P028.002.E701		Linear Halls execution

Accessories		
Part No.	Name	Description
P038.002.E306	CAN terminator	Molex MFIT 2x2 connector with 120 Ohms terminal resistor
P028.040.C232	CA RS232 cable	Molex 2x2 M-Fit to DB9 cable
P028.040.C030	CAN interconnection	CAN2CAN Cable 10cm Molex 2x2 M-Fit drive to drive
P038.001.E136	RS232 - USB adapter	Standard USB to RS232 adapter with FTDI chipset

Ordering information			
Part No.	Description	Package components	Connectors
P028.040.C099	CCS iPOS360x BXD (Complete cable set, 100 cm with differential encoder cable)	1 x Motor & Hall cable	J2
		1 x Supply cable	J1
		2 x CAN cable / RS232 cable	J5, J6 / J7
		1 x I/O cable	J4
		1 x Differential Encoder cable or Linear Hall cable	J3
P028.040.C098	CCS iPOS360x BXE (Complete cable set, 100 cm with single-ended encoder cable)	1 x Motor & Hall cable	J2
		1 x Supply cable	J1
		2 x CAN cable / RS232 cable	J5, J6 / J7
		1 x I/O cable	J4
		1 x Single-ended Encoder cable	J3

Name ALN	First edition November 20, 2020	Document template: P099.TQT.564.0001	Last edition May 14, 2025	Visa:
		iPOS360x BX-CAN Cable Set PRODUCT DATA SHEET		P028.040.C09x.BX.DSH.10C Page : 1 of 2

J1 - Power Supply cable				
	Connector's view from crimp pins entry side	Connector's lateral view	1 - white 2 - brown AWG 24	
J2 - Motor and Hall Inputs cables V2*				
	Connector's view from crimp pins entry side	Connector's lateral view	Motor cable 1 - red 2 - yellow 6 - blue 7 - yellow/green 9 - black Shield connected to housing pin 9 AWG 20	
			Hall Inputs cable 3 - red 4 - yellow 5 - brown 8 - green 10 - orange AWG 24	
J3 - Differential Encoder cable or Linear Hall cable				
	Connector's view from crimp pins entry side	Connector's lateral view	Twisted pairs 1 - 2 5 - 6 7 - 8 9 - 10 Notice: pins/wires 3 - 4 are missing. Only 8 wires are used. 1 - white 2 - brown 5 - green 6 - yellow 7 - gray 8 - pink 9 - blue 10 - red AWG 30	
J3 - Single-Ended Encoder cable				
	Connector's view from crimp pins entry side	Connector's lateral view	1 - white 2 - brown 6 - green 8 - yellow 10 - gray Shield connected to housing pin 3 AWG 30	
J4 - Inputs/Outputs cable				
	Connector's view from crimp pins entry side	Connector's lateral view	1 - white 2 - brown 3 - green 4 - yellow 5 - gray 6 - pink 7 - blue 8 - red 9 - black 10 - violet 11 - gray-pink 12 - red-blue 13 - white-green 14 - brown-green AWG 24	
J5, J6, J7 - RS232 or CAN cable				
	Connector's view from crimp pins entry side	Connector's lateral view	1 - white 2 - brown 3 - green 4 - yellow AWG 24	
Cables description - Cables length 1000 mm; - Stripped wires 5 mm; - One end with flying leads (20mm). * The color scheme shown applies to the V2 version of the cables, which will be commercially available starting May 2025. For documentation on the previous color scheme, please contact Technosoft.				

Name ALN	First edition November 20, 2020	Document template: P099.TQT.564.0001	Last edition May 14, 2025	Visa:
 TECHNOSOFT		Title of document iPOS360x BX-CAN Cable Set PRODUCT DATA SHEET	N° document P028.040.C09x.BX.DSH.10C	
			Page : 2 of 2	