



2/3" 1.4/16mm C		2/3"	1/1.8"	1/2"
FOCAL LENGTH		f=16mm		
MAX. DIAMETER (RATIO)		F=1:1.4,4,8,16		
ELEMENT		7 8		
PICTURE SIZE		6.6x8.8mm	5.4x7.2	4.8x6.4
ANGLE	VER. ANGLE	22.7°	18.6°	16.4°
	HOR. ANGLE	30.0°	24.7°	21.8°
	DIA. ANGLE	37.0°	30.9°	27.0°
DISTORTION (TV)		-0.05%		
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	84.4mm	68.7	61.2
	HOR.	112.8mm	91.8	81.8
	DIA.	141.2mm	114.9	102.5
MINIMUM FOCUS DISTANCE		0.2m		
FLANGE BACK		17.526 mm in air		
BACK FOCUS		13.1mm in air (Mechanical 13.1mm in air)		
FILTER SCREW SIZE		M27x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 20.2mm		REAR ϕ 15.5mm
MOUNT		C-MOUNT		
EXIT PUPIL		338.4mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 120lp/mm		CORNER 100lp/mm
WEIGHT		76.5g		

NOTE: Specifications and availability are subject to change without notice.



		1/1	
		2/3" F1.4 f=16mm	
2014.12.26		LM16JCM-V	
2014.6.9			