



Identification	Type	LCIS-WP-WUAA-1517-175-PI
	Part-No.	751517.0000
Description		
	Input: 16 selectable ranges	
	Output: 0–10 V / 0–20 mA / 4–20 mA	
	Insulation: 4 kV, 3-way isolation, Wide range input	
Input		
Input signal	0–60, 0–100, 0–300, 0–500 mV adjustable via DIP switch S1 0–1, 0–2, 0–5, 0–10, 0–20, 2–10 V adjustable via DIP switch S1 0–5, 0–10, 0–20, 4–20, ±5, ±20 mA adjustable via DIP switch S1	
Galvanic isolation I/O	3-way isolation	
Zero /Span	Production comparison	
Input resistance	>330 kΩ @ mV, V, <100 Ω @ mA	
Output		
Output signal	0–10 V, 0–20 mA, 4–20 mA, adjustable via switch	
Output voltage limit	min 0 V max 10.8 V for all output ranges with nominal upper limit 10 V	
Output current limit	min. 0 mA for all output ranges with nominal lower limit 0 mA min. 3.6 mA or all output ranges 4 – 20 mA max. 21.6 mA for all output ranges with nominal upper limit 20 mA	
Max. load impedance at I-output	500 Ω @ 0–20 mA, 4–20 mA	

13.02.2020 – Subject to technical modification

Part-No. 751517.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · Interface Technology

Min. load impedance at U-output	2 k Ω @ 0–10 V
Load deviation	at U-output max. 5 mV @ 2 k Ω
Output voltage	<18 V @ 0–20 mA, 4–20 mA
Output current	max. 5 mA @ 0–10 V
Residual ripple	<20 mV _{eff}

Operating data

Accuracy	0.1 % FSR @ 23 °C
Linearity error	0.05 % FSR
Rise time (10 - 90%)	6 ms
Build-up time (Accuracy 1%)	17 ms
Temperature coefficient	<150 ppm / K FSR
Critical frequency	30 Hz @ 3 dB

General

Rated voltage U _N	AC/DC 24–240 V
Operation voltage range	AC 19.2–264 V / DC 18.0–264 V
Status indication	LED green
Input/output protection	Overvoltage, current input with PTC fuse, short circuit-proof output
Insulation voltage input / output	4.0 kV _{eff}
Housing material	PA 6.6 (UL 94 V-0, NFF I2, F2)
Color of the housing	RAL 7012 basalt grey
Mounting	DIN rail mountable TS35 (EN 60715)
Protection class	IP20
Installation position	any
Connection type	Push-In single wire 0.25 mm ² –2.5 mm ² / AWG 20–14 fine stranded wire with ferrule 0.25 mm ² –1.5 mm ² / AWG 20–16
Operation temperature range	-25 °C ... +60 °C
Storage temperature range	-40 °C ... +80 °C
Dimensions (w × h × d)	17.5 × 93.0 × 73.0 mm
Weight	0.059 kg/piece
PU	1 piece
Certifications	cULus (E135145) DNV GL
Standards	EN 60947-5-1
PU	1 piece

Failure Rate Prediction (MTBF)

13.02.2020 – Subject to technical modification

Part-No. 751517.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

Technical data sheet · Interface Technology

Standards	Electronic components – Reliability – Reference conditions for failure rates and stress models for conversion: EN/IEC 61709 Failure Rates of Components – Expected values: SN 29500
Failure rate at +45 °C	681 fit
Failure rate at +45 °C	1468511 h
	1 fit equals one failure per 10 ⁹ component hours
	The indicated temperature is the mean component ambient temperature.
Comments	The results are valid under following conditions: Automotive environment or industrial areas without extreme dust levels and harmful substances Continuous operation 8760 h per year

Dimensions



13.02.2020 – Subject to technical modification

Part-No. 751517.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2


www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · Interface Technology


PIN assignment



Range adjustment

S1	Input
●→Switch On	1 2 3 4
0-60 mV	•
0-100 mV	•
0-300 mV	•
0-500 mV	•
0-1 V	•
0-2 V	•
0-5 V	•
0-10 V*	•
2-10 V	•
0-20 V	•
0-5 mA	•
0-10 mA	•
±5 mA	•
±20 mA	•
0-20 mA	•
4-20 mA	•

S1	Output
●→Switch On	5 6
0-10 V*	•
0-20 mA	•
4-20 mA	•



13.02.2020 – Subject to technical modification

Part-No. 751517.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY