

Plastic connector, quick-type
straight, outer thread, conically sealed

EIGENSCHAFTEN

- beständig gegen Öl und Benzin
- weitgehend säure- und lösungsmittelbeständig
- silikon-, cadmium- und halogenfrei

PROPERTIES

- resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen

 IP 66
 -40°C ... +120°C

EN / IEC 61386-23



UL 1696

UR file E86359



CSA 22.2

File No. 227.3-05



FLEXA No.	FLEXA No.	AD OD								
schwarz black	grau grey	ø		øl mm	øB mm	C mm	D mm	SW mm	kg 100	St. pcs.
RQG1–M			Metr. EN 60423						[IP 66]	
5020.055.210	5020.055.010	10,0	M 10 x 1,0	6,0	17,0	11,5	34,5	16	0,400	50
5020.055.211	5020.055.011	10,0	M 12 x 1,5	7,0	17,0	11,5	34,5	16	0,400	50
5020.055.212	5020.055.012	13,0	M 12 x 1,5	7,0	20,0	12,0	37,0	18	0,520	50
5020.055.214	5020.055.014	13,0	M 16 x 1,5	10,0	20,0	11,5	37,0	18	0,560	50
5020.055.216	5020.055.016	15,8	M 16 x 1,5	11,0	23,0	11,5	39,0	21	0,700	50
5020.055.218	5020.055.018	15,8	M 20 x 1,5	12,0	25,0	13,0	39,0	21	0,760	50
5020.055.219	5020.055.019	18,5	M 20 x 1,5	13,5	26,0	13,0	43,0	24	0,880	50
5020.055.220	5020.055.020	21,2	M 20 x 1,5	16,0	29,5	13,0	44,5	27	1,160	50
5020.055.222	5020.055.022	21,2	M 25 x 1,5	17,0	29,5	13,0	44,5	27	1,240	50
5020.055.225	5020.055.025	28,5	M 25 x 1,5	19,5	37,0	13,0	47,0	34	1,750	25
5020.055.228	5020.055.028	28,5	M 32 x 1,5	23,0	37,0	15,0	49,0	34	1,800	25
5020.055.232	5020.055.032	34,5	M 32 x 1,5	25,5	44,0	15,0	51,0	40	2,400	25
5020.055.236	5020.055.036	34,5	M 40 x 1,5	30,5	48,5	15,0	51,5	40	2,560	25
5020.055.240	5020.055.040	42,5	M 40 x 1,5	32,0	52,0	15,0	53,5	48	3,360	25
5020.055.245	5020.055.045	42,5	M 50 x 1,5	36,5	56,0	15,5	55,0	48	3,700	10
5020.055.250	5020.055.050	54,5	M 50 x 1,5	42,5	63,5	15,5	55,0	59	4,200	10
5020.055.263	5020.055.063	54,5	M 63 x 1,5	48,0	70,0	16,0	55,0	59	5,250	10
Kleine Packungseinheit		small packing unit								
5020.755.211		10,0	M 12 x 1,5	7,0	17,0	11,5	34,5	16	0,400	10
5020.755.214		13,0	M 16 x 1,5	10,0	20,0	11,5	37,0	18	0,560	10
5020.755.218		15,8	M 20 x 1,5	12,0	25,0	13,0	39,0	21	0,760	10
5020.755.222		21,2	M 25 x 1,5	17,0	29,5	13,0	44,5	27	1,240	10
5020.755.228		28,5	M 32 x 1,5	23,5	37,0	15,0	49,0	34	1,800	10
5020.755.236		34,5	M 40 x 1,5	30,5	48,5	15,0	51,5	40	2,560	2
5020.755.245		42,5	M 50 x 1,5	36,5	56,0	15,5	55,0	48	3,700	2
5020.755.263		54,5	M 63 x 1,5	48,0	70,0	16,0	55,0	59	5,250	2
RQG1–P			PG DIN 40430						[IP 66]	
5020.049.207	5020.049.007	10,0	7	7,0	17,0	10,0	32,5	16	0,420	50
5020.063.202		10,0	9	7,0	18,5	10,0	32,5	16	0,420	50
5020.063.203		10,0	11	7,0	21,0	10,0	32,5	16	0,480	50
5020.063.205		10,0	13,5	7,0	23,0	10,0	32,5	16	0,560	25
5020.062.201		13,0	7	8,0	20,0	10,0	35,0	18	0,520	50
5020.049.209	5020.049.009	13,0	9	10,0	20,0	10,0	35,0	18	0,520	50
5020.063.204		13,0	11	10,0	21,0	10,0	35,0	18	0,560	50
5020.063.206		13,0	13,5	10,0	23,0	10,0	35,0	18	0,600	25
5020.049.211	5020.049.011	15,8	11	12,5	23,0	10,0	37,0	21	0,700	50
5020.063.207		15,8	13,5	12,5	23,0	10,0	37,0	21	0,720	25
5020.063.210		15,8	16	12,5	26,5	10,0	37,0	21	0,800	25
5020.049.213	5020.049.013	18,5	13,5	13,5	26,0	13,0	43,0	24	0,880	50
5020.062.209		21,2	13,5	15,4	29,5	13,0	43,5	27	1,200	10
5020.049.216	5020.049.016	21,2	16	17,0	29,5	13,0	46,0	27	1,240	50
5020.062.208		28,5	16	17,0	37,0	12,0	48,5	34	1,800	10
5020.049.221	5020.049.021	28,5	21	23,0	37,0	12,5	48,5	34	1,680	25
5020.049.229	5020.049.029	34,5	29	30,0	44,0	14,5	53,5	40	2,400	25
5020.049.236	5020.049.036	42,5	36	36,5	51,5	14,5	56,0	48	3,120	25
5020.049.248	5020.049.048	54,5	48	48,0	65,5	15,5	58,0	59	4,400	10

