

hybrid motor starter, 3-pole (36110)



The picture may show a similar product.



Description

Part No.: **36110**000A

MOTUS® CrossBoard

hybrid motor starter, 3-pole

electronic unit direct and reversing starter 0.18 - 2.4 A / switch for resistive loads 0.18 - 2.4 A

with CrossLink® interface

System

CrossBoard®

Product group 21

Subgroup 01

pack size 1

EAN 4021267361105

catalog page 2020 : 1.2, 2.3, 3.16, 6.1

ECLASS 6.1 27370804

ECLASS 7.1 27370804

ETIM 4.0 EC001037

ETIM 5.0 EC001037

Approvals

Standards

EN 60947-1:2015

EN 60947-4-2:2012

EN 61439-1:2012

EN 50581:2012

EN ISO 13849-1:2015

UL 60947-1

Approvals

UL , CCC , EAC , Atex



for UL feeder circuits >250V

type number: 36110.1

EAC Type: MCC

UL file: E360470, UL category (for USA): NLDX <https://www.ul.com>

UL file: E360470, UL category (for Canada): NLDX7 <https://www.ul.com>

CCC certificate: 2019010304252617

Type-Examination Certificate: PTB13AT3001

Technical data

Details IEC

Standards

EN 60947-1:2015

EN 60947-4-2:2012

EN 61439-1:2012

EN 50581:2012

EN ISO 13849-1:2015

Electrical data IEC

Rated current (IEC): 2.4 A

rated voltage (IEC) AC: 500 V

min. operating voltage AC: 42 V

trigger characteristic: Class 10A

set nominal current: Yes

min. load current: 0.18 A

max. switching frequency: 2 Hz

switching cycles: 30.000.000

safety level: SIL3

reply contact: 1 CO

rated frequency (IEC): 50 / 60 Hz

rated isolation voltage U_i AC: 500 V

rated surge voltage U_{imp} : 6 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 3.5 W.

(The power dissipation at full load would be 5.5 W.)

Details UL

Standards

UL 60947-1

for UL feeder circuits >250V

Electrical data UL

rated current (UL): 2 A
rated voltage (UL) AC: 500 V
min. operating voltage AC: 42 V
rated frequency (UL): 50 / 60 Hz

SCCR unprotected max.: 5 kA
3 cycles (without OPD) @ 600 V AC
SCCR protected max.: 100 kA

SCCR: 100 kA with JDDZ fuse Class J 175 A / 600 V AC

Mechanical data

W x H x D: 22.5 x 160 x 120
weight: 50.7 kg/100
poles: 3-pole

degree of protection: IP20

vertical installation position: Yes
horizontal installation position: No

permitted degree of pollution: 2

Terminal points

screw clamp connection
screw drive: 0,8x4
wire stripping: 8 mm
min. cross-section: 0.2 mm²
max. cross-section: 2.5 mm²
Md min.: 0.5 Nm
Md max.: 0.6 Nm

min. cross-section UL: AWG 24
max. cross-section UL: AWG14
torque (UL): 4,4 - 5,3 lb-in

Accessories



31567000

replacement fuse for MOTUS®

fuse 16 A for version 0.6 A and 2.4 A

10x38 gR